



MATERIAL:

- SHELL : DIE CAST ALUMINUM ALLOY PER SAE AMS-QQ-A-591
- INSERT RETENTION PLATES : ALUMINUM ALLOY PER SAE AMS-QQ-A-250 OR QQ-A-591
- C2 INSERT : ALUMINUM ALLOY PER SAE AMS-QQ-A-250 OR QQ-A-591
- 57 INSERT : THERMOSETTING MOLDED COMPOUND PER ASTM D 5948
- SEPARATOR SEAL (for 57 insert) : FLUOROSILICONE ELASTOMER PER SAE AMS-R-25988
- CONTACT RETENTION CLIPS : BERYLLIUM COPPER PER ASTM B 194
- POLARIZING POSTS : STAINLESS STEEL PER ASTM-A-581
- CONTACTS : BERYLLIUM COPPER PER ASTM B 196
- PROTECTIVE SLEEVE : STAINLESS STEEL PER SAE AMS-5514
- SCREWS AND WASHERS : CORROSION RESISTANT MATERIAL

FINISH :

- SHELL : YELLOW CHROMATE OVER CADMIUM PER SAE AMS-QQ-P-416, TYPE II
- C2 INSERT : WHITE CHROMATE OVER CADMIUM PER SAE AMS-QQ-P-416, TYPE II
- INSERT RETENTION PLATES : YELLOW ANODIZED PER MIL-A-8625
- CONTACT BODY : PLATING .00005 INCH OF GOLD PER SAE AMS-2422 OVER NICKEL PER AMS 2403
- PROTECTIVE SLEEVE : PASSIVATED PER SAE AMS-QQ-P-35

CONNECTOR FITTED WITH :

- CAVITY B : 59 SIZE 20 REAR RELEASE, REAR REMOVABLE CRIMP SOCKET CONTACTS P/N : 610325 (UNINSTALLED)
- MARKING : CONNECTOR AND PACKAGING MUST BE MARKED WITH : DSX2H35X21S73** + DATE CODE
CODE ** : ** SEE NOTE 1 (PAGE 1/2)
- INDIVIDUAL PACKAGING

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from RADIALL. This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.

4112_9311