

Build-Out Optical Attenuators, SC

SC, 18 dB

CORNING

Corning universal build-out optical attenuators are used to interconnect single-mode connectors with or without attenuation. The SC attenuator styles are available in 0-16, 18 and 20 dB levels. Each build-out attenuator requires the use of a build-out block (sold separately) that replaces the standard adapter. The SC build-out block has molded latches for snap mounting into SC panels. The unique design of these attenuators allows for easy change-out of attenuation values with no tools required, and the 0 dB offering is very useful for connections where no additional attenuation is required.

Features and Benefits

Dual-wavelength design

Operable at 1310 and 1550 nm

Easy change-out of attenuation values

No tools required

Single-mode precision sleeve

Provides precise alignment

Molded latches

Snap mount into SC panels



Part Number: ATN-38U-BO-18



Part Number: ATN-38U-BO-18

Build-Out Optical Attenuators, SC

SC, 18 dB

CORNING

Specifications

General Specifications

Attenuator Type	Build-Out
Compatibility	SC
Packaging	Single Pack
Product Type	Attenuators

Temperature Range

Operation	-40 °C to 65 °C (-40 °F to 149 °F)
-----------	------------------------------------

Design - Connector

Housing Material	Composite
------------------	-----------

Optical Specifications - Connector

Attenuation	18 dB
Attenuation Tolerance	± 2.7 dB
Reflectance	≤ -40 dB

Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	ATN-38U-BO-18
Product Description	SC Build-Out Optical Attenuator

Shipping Information

Units per Delivery	1/1
Package Contents	Attenuator, SC

Build-Out Optical Attenuators, SC

SC, 18 dB

The CORNING logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font centered inside.

Notes



**Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea**

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2014 Corning Optical Communications. All rights reserved.