

In-Line Optical Attenuators, Flat Wavelength, LC UPC

LC UPC, 12 dB

CORNING

Corning offers in-Line, flat wavelength optical attenuators that are easily inserted between the connector and adapter in an “in-line” configuration and are compatible with SC, ST[®] compatible, FC, MU, LC and angled SC and FC connectors. A fundamental element of these Corning attenuators is the zirconia ferrule containing a specially selected attenuating fiber. This special fiber minimizes the effect of modal interference and gives the component a flat spectral response. It is extremely stable over the wavelength range of 1260 to 1360 nm and 1430 to 1580 nm. These in-line, flat wavelength attenuators are available in ultra PC (\leq -55 dB) and angled PC (\leq -65 dB) finish to meet the most demanding network reflectance requirements.

Features and Benefits

Fully compatible with LC fiber optic connectors
No intermateability concerns

Numerical identification mark on housing
Easy indication of attenuation levels

Attenuator incorporated inside standard LC adapter housings
Compatible with standard distribution panels

Standards

Design and Test Criteria Telcordia GR-910 issue 2 performance requirements



Part Number: ATN-A10-12



Part Number: ATN-A10-12

In-Line Optical Attenuators, Flat Wavelength, LC UPC

LC UPC, 12 dB

CORNING

Specifications

General Specifications

Attenuator Type	In-Line
Compatibility	LC
Packaging	Single Pack
Product Type	Attenuators

Temperature Range

Operation	-25 °C to 70 °C (-13 °F to 158 °F)
-----------	------------------------------------

Design - Connector

Ferrule Material	Zirconia
Housing Material	Composite
Housing Color	Blue

Optical Specifications - Connector

Attenuation	12 dB
Attenuation Tolerance	± 1.2 dB
Insertion Loss	1.2 dB

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Ordering Information

Part Number	ATN-A10-12
Product Description	LC UPC In-Line Optical Attenuator, Flat Wavelength
EAN Code	4056418188645

In-Line Optical Attenuators, Flat Wavelength, LC UPC

LC UPC, 12 dB



Shipping Information

Units per Delivery	1/1
Package Contents	Attenuator, LC UPC



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.