


# Photocells B 1060, V 1060

## Metal housing TO types





Street Light control

Combustion control

This range of Photocells includes metal housings in 2 different sizes, TO-8 and TO-5.

Operating Temperature Range: -20...+70 °C (non continuous)




Storage Temperature Range: -20...+80 °C (non continuous)



Type	R <sub>10</sub>	R <sub>100</sub>	R <sub>01</sub>	R <sub>05</sub>	V <sub>max</sub>	P <sub>max</sub>	γ <sub>10/100</sub>	λ <sub>peak</sub>
units	KΩ	KΩ typ.	MΩ min	MΩ min	V	mW	typ.	nm
B 1060 23	4...15	1,6	0,1	0,3	300	90	0,8	600
V 1060 21	2,9...5,5	1,0	0,02	0,06	150	90	0,8	600
V 1060 21	5...9	1,6	0,06	0,18	150	90	1,30,9	600
V 1060 31	40...120	25	0,5	1,5	300	90	0,6	600
V 1060 32	100...220	35	1,0	3,0	300	90	0,65	600

B 10...

V 10...



all  
Dimensions  
in mm.

Europe:  
PerkinElmer Optoelectronics  
GmbH & CoKG  
Wenzel Jaksch Str 31  
65199 Wiesbaden / Germany  
Phone +49(0)611 492 0  
Fax +49(0)611 492 170

USA:  
PerkinElmer Optoelectronics  
44370 Christy Street  
Freemont, CA 94538-3180  
Phone +510 979 6500  
+800 775 6786  
Fax +510 687 1140

Asia:  
PerkinElmer Optoelectronics  
47, Ayer Rajah Crescent #06-12  
Singapore 139947  
Phone +65 775 2022  
Fax +65 775 1008

**EXCELITAS**  
TECHNOLOGIES

