

Flag Terminals





KRIMPTITE® UNINSULATED		Part Number	Wire Size	Tab	A Max.	B Max.	C Ref.	D	MW/D
	AA-1158	22-18 (0,25-1,3)	250X 032 (6,3X0,8)	.562 (14,3)	.321 (8,1)	.079 (2,0)	.305 (7,7)		
		16-14	250X 032	.562	.321	.079	.305		
	BB-1159	22-18 (1,0-2,6)	187X 032 (4,7X0,8)	.562 (14,3)	.321 (8,1)	.040 (2,0)	.250 (7,7)		
	AA-1147-032	16-14 (0,25-1,3)	187X 032 (4,7X0,8)	.562 (14,3)	.321 (8,1)	.040 (1,0)	.250 (6,3)		
	BB-1148-032	22-18 (1,0-2,6)	187X 032 (4,7X0,8)	.562 (14,3)	.321 (8,1)	.040 (1,0)	.250 (6,3)		
	AA-1147	16-14 (0,25-1,3)	187X 020 (4,7X0,5)	.562 (14,3)	.321 (8,1)	.040 (1,0)	.250 (6,3)		
	BB-1148	22-18 (1,0-2,6)	187X 020 (4,7X0,5)	.562 (14,3)	.321 (8,1)	.040 (1,0)	.250 (6,3)		
		16-14	187X 020	.562	.321	.040	.250		
		22-18	187X 020	.562	.321	.040	.250		
		16-14	187X 020	.562	.321	.040	.250		
VIBRAKRIMP® WITH WIRE GRIP		Part Number	Wire Size	Tab	A Max.	B Max.	C Ref.	D	MW/D
	AA-4168	22-18 (0,25-1,3)	250X 032 (6,3X0,8)	.568 (14,4)	.385 (9,8)	.079 (2,0)	.305 (7,7)	.135 (3,4)	
		16-14	250X 032	.562	.385	.079	.305	.145	
	BB-4169	22-18 (1,0-2,6)	187X 032 (4,7X0,8)	.568 (14,3)	.385 (9,8)	.040 (2,0)	.250 (7,7)	.135 (3,7)	
	AA-4170-032	16-14 (0,25-1,3)	187X 032 (4,7X0,8)	.562 (14,4)	.385 (9,8)	.040 (1,0)	.250 (6,3)	.145 (3,4)	
	BB-4171-032	22-18 (1,0-2,6)	187X 032 (4,7X0,8)	.568 (14,3)	.385 (9,8)	.040 (1,0)	.250 (6,3)	.145 (3,7)	
	AA-4170	16-14 (0,25-1,3)	187X 020 (4,7X0,5)	.568 (14,4)	.385 (9,8)	.040 (1,0)	.250 (6,3)	.145 (3,4)	
	BB-4171	22-18 (1,0-2,6)	187X 020 (4,7X0,5)	.562 (14,3)	.385 (9,8)	.040 (1,0)	.250 (6,3)	.145 (3,7)	
		16-14	187X 020	.562	.385	.040	.250	.145	
		22-18	187X 020	.562	.385	.040	.250	.145	
		16-14	187X 020	.562	.385	.040	.250	.145	

NOTE: For uninsulated Flag Terminals on Mylar Tape, add "T" at the end of loose piece Part Number.

Flag Quick Disconnect Receptacles

MATERIAL: TIN-PLATED BRASS



KRIMPTITE® Economical - No Vibration Support			Hand Tool Only
Use With Tab Size	AWG Wire Range	mm ²	Crimping Tool No.
.187 x 020 (4,7 x 0,5)	16-14	1,0-2	RHT-FFQD
.250 x 032 (6,4 x 0,8)	18-14	1,0-2	RHT-FFQD
.250 x 032 (6,4 x 0,8)	14-12	1,6-4	RHT-B175

Use With Tab Size	AWG Wire Range	mm ²	Width W	Crimp B	Length L	Part No.	Fig.	Crimping Tool No.
.187 x 020 (4,7 x 0,5)	16-14	1,0-2	.227 (5,8)	.221 (5,6)	.457 (11,6)	A-174	1	RHT-FFQD
.250 x 032 (6,4 x 0,8)	18-14	1,0-2	.307 (7,8)	.239 (6,1)	.515 (13,1)	FFT-1	1	RHT-FFQD
.250 x 032 (6,4 x 0,8)	14-12	1,6-4	.312 (7,9)	.307 (7,8)	.593 (15,1)	B-175	2	RHT-B175

