



Plug

SNP-8 Series
Angle PC Application
Easy Assembly
Designed for
ø 0.9 mm Buffer Cable
ø 2.0 mm Cable
ø 3.0 mm Cable
Single Mode

- ▶ Housing designed for Angle PC application
- ▶ Uses a zirconia ferrule having a conical tip optimal for angle PC polishing
- ▶ Angled endface shape for easier polishing
- ▶ Keying width: 2.14 + 0/-0.05 mm (N type); 2.02+0/-0.05 (R type)
- ▶ Complies with Telcordia specification GR-326-CORE (excluding Ø 0.9 mm rubber hood type)
- ▶ Combined with SNA-1/3/4 (Adaptor) provides low insertion loss and ultra high return loss
- ▶ Satisfy Vertical Burning Test for Classifying Materials UL94V-0 (excluding cap)

ORDERING INFORMATION

Model Number	Type Number									
SNP-8	8	7	1	2	5	1	B	3	0	1
Hood Color								Specification		
0 Black								01 Cutout frame N type		
8 Green								D1 Molded frame N type		
								J1 Cutout frame R type		
								K1 Molded frame R type		
Hood I.D. (mm)								Package		
1	0.9 mm (flame-resistant rubber)							1 Individual Package		
7	3.0 mm (Plastic)							3 Bulk Package		
6	2.0 mm (Plastic)									
9	0.9 mm (Plastic)							Cap		
Ferrule I.D. (μm)								0 No Cap		
ø 125, ø 126								8 Green PVC		
								B Green Ferrule Cap		
Marking of Hood										