

Product data sheet

Characteristics

XUYFVERTL101

glass fibre optic for sensor - thru-beam - lateral -
High temp - 1m - Sn200mm

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 278.00 USD



Main

Range of product	OsiSense XU
Sensor name	XUY
Sensor design	Fiber design
Sheath type	High temperature
[Sn] nominal sensing distance	7.87 in (200 mm) XUYAFV
End fitting type	Lateral with nickel plated brass, M4 x 0.7

Complementary

Electronic sensor type	Photo-electric sensor
Optic fiber material	50 µ glass
Sheath material	Flexible stainless steel
Detection system	Thru beam
Optic fiber length	3.28 ft (1 m)
Minimum bending radius	1.18 in (30 mm)
Head mounting	M4 x 0.7


Environment

Ambient air temperature for operation	-13...392 °F (-25...200 °C)
---------------------------------------	-----------------------------

Ordering and shipping details

Category	22481 - SENSORS, PHOTOELECTRIC
Discount Schedule	DS2
GTIN	003389119008372
Nbr. of units in pkg.	1
Package weight(Lbs)	0.11
Returnability	N
Country of origin	FR

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0647 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
- - - - - Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
- - - - - Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
- - - - - More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------