





# TSRK4/10

- 10 Connections
- 10 Screw Connections

## Technical Data

Wire sizes		Insulating Material	
Solid min	0.2 mm <sup>2</sup>	Material	PA 6.6
Solid max	6.0 mm <sup>2</sup>	Flammability Class	UL 94 V-0
Stranded (flexible) min	0.2mm <sup>2</sup>	Temperatures	
Stranded (flexible) max	6.0 mm <sup>2</sup>	Working Temperature	-40 - 120 °C
Stranded with Ferrule min	0.2 mm <sup>2</sup>	Dimensions	
Stranded with Ferrule max	4.0 mm <sup>2</sup>	Stripped Length	9.0 mm
Clamping Range min	0.2mm <sup>2</sup>	Width	75.0 mm
Clamping Range max	6.0 mm <sup>2</sup>	Height	33.1 mm
		Length	20.5 mm

## Colours

-  ORANGE, similar RAL 2003
-  BEIGE, similar RAL 1019

## Connection Diagram



## Order Data

Article Designation	Article Number	PU
TSRK4/10-ORANGE	41150.3	5
TSRK4/10-BEIGE	41150.2	5

## Accessoires

Article Designation	Article Number	PU
Quick Labelling PSB7.5/40	499326.7	400
Quick Labelling PSB7.5/40-B	493327.7	400

## Ratings

Ratings	CSA	CSAus	IEC
Rated Voltage	600 V	600 V	800 V
Rated Current	30 A	30 A	32 A
Rated Wire Size	AWG 22-10	AWG 22-10	4.0 mm <sup>2</sup>
Rated Impulse Voltage			8 V
Pollution Degree			3