



ZR2.5-DRL-EL=D1

- 2x2 Connections
- With electronic components


Technical Data

Wire sizes		Insulating Material	
Solid min	0.5 mm ²	Material	PA 6.6
Solid max	4.0 mm ²	Flammability Class	UL 94 V-0
Stranded (flexible) min	0.5mm ²	Temperatures	
Stranded (flexible) max	4.0 mm ²	Working Temperature	-40 - 120 °C
Stranded with Ferrule min	0.5 mm ²	Dimensions	
Stranded with Ferrule max	2.5 mm ²	Width	5.1 mm
		Length	83.6 mm
		Height TS35 x 7.5	39.0 mm

Electrical Data

General		Diodes	
Cross Connection Channels	1	Diode Type	1N4007
Test Pick off	2	Diode Reverse Voltage	1.000 V
		Diode Current	1 A

Colours

 BEIGE, similar RAL 1019

Connection Diagram



Order Data

Article Designation	Article Number	PU
ZR2.5-DRL-EL=D1-BEIGE	43504.2	100

Accessoires

Article Designation	Article Number	PU
End Plate ZAP2.5/4A	493702.2	50
Four-Way Covers ZAD2.5/4/B	493706.0	20
End Stopn ZES35	493748.2	50
Test Adapter ZTA2.5	493740.2	10
Quick Labelling PSB5/50	494600.7	500

Ratings

Ratings	CSA	CSAus	IEC
Rated Voltage	600 V	600 V	800 V
Rated Current	27 A	27 A	24 A
Rated Wire Size	AWG 20-12	AWG 20-12	2.5 mm ²
Rated Impulse Voltage			8 V
Pollution Degree			3