


SD



NOTES:

1. FOR USE WITH RG-55A, 142, 223/U CABLE.
2. FOR CRIMPING USE DIE KTH-2001.
3. FOR CABLING INSTRUCTONS SEE CP-403.
4. MARK PACKAGE: KINGS KD-59-63
YRWK (DATE CODE)
5. MATERIALS:
INSULATOR: TEFLON, ASTM-D-1457
GASKET: SIL. RUB., ZZ-R-765
K-GRIP SLEEVE: COM. BRONZE TUBE, ALLOY 220
OUTER CONTACT BER. COP., QQ-C-530
SPRING WASHER BER. COP., QQ-C-533
ALL OTHER METAL PARTS: BRASS, QQ-B-626
6. FINISHES:
CENTER CONTACT: HARD GOLD PLT. PER MIL-G-45204
ALL OTHER METAL PARTS: SILVER PLATE , QQ-S-365
7. ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS
VOLTAGE RATING: 1000 VRMS
FREQUENCY RANGE: DC TO 11 GHz

STAMP: KINGS KD-59-64
YRWK (DATE CODE)

KD-59-63

REVISIONS

ISSUE	CHANGES	
	DATE	DESCRIPTION
1	CN 115142 A JL 02/06/76	
1	CN 19900 A MA 12/06/79	
3	CN 37575 C REDRAWN MK 02/11/99	
4	CN 38134 E HVN 12/06/00	

SCALE 4:1

APPROX SURFACE AREA

USED ON

REF:

C-PLUG

DRAWN	HFE	DATE	12/27/66
DESIGN	PETE	DATE	12/27/66
APPR.		DATE	

KINGS
ELECTRONICS CO., INC.
TUCKAHOE, NEW YORK 10707

KD-59-63

SD