


Preliminary data

- RF Switch up to 2 GHz
- Available in Chip Version up to 12 GHz
- 1 ns Rise/Fall Time
- Low Loss
- High Isolation
- High Input Power Capabilities



Type No.


Marking

Ordering code, tape & reel

Package ¹⁾

CSY 10

MW-7

**Maximum ratings**

Channel temperature

 T_{ch}

150

°C

Storage temperature range

 T_{stg}

-55 to 150

°C

Control voltage

 V_C

-8

V

Input power (0,01 GHz)

 P_{in}

+ 22

dBm

(0,5 - 12 GHz)

 P_{in}

+ 29

dBm

Thermal resistance

Channel to soldering point (GND)

 R_{thChS}

≤

K/W

1) For detail dimensions see pg. 4

Electrical characteristics

at $T_a = 25^\circ\text{C}$ (All specifications apply with $50\ \Omega$ impedance at all parts with control Voltage $V_c = 0 / -5\ \text{V}_{dc}$, if not otherwise specified)

		min	typ	max	Units
Insertion Loss ($R_{Fin} - R_{F1or2}$)	L	-	0.6	-	dB
10 MHz		-	0.7	-	
450 MHz		-	0.8	-	
900 MHz		-	1.2	-	
1.8 GHz		-		-	
Isolation ($R_{Fin} - R_{F1or2}$)	I	-	60	-	dB
10 MHz		-	35	-	
450 MHz		-	30	-	
900 MHz		-	22	-	
1. GHz		-		-	
Return Loss	R	-	14	-	dB
10 MHz - 1000 MHz		-	10	-	
1.8 GHz		-		-	
Input power at which insertion loss compresses by 1 dB	$P_{in(-1dB)}$	-	17	-	dBm
10 MHz		-	22	-	
250 MHz		-	26	-	
900 MHz		-	27	-	
1.8 GHz		-		-	
Switching characteristics	t	-	1	-	ns
t_{rise}, t_{fall}		-	2	-	
t_{on}, t_{off}		-		-	


Truth Table

Control input		Condition of switch	
C1	C2	$R_{Fin} - R_{F1}$	$R_{Fin} - R_{F2}$
0 V	-5 V	off	on
-5 V	0 V	on	off

Electrical characteristics (Chip)


at $T_a = 25^\circ\text{C}$ (All specifications apply with $50\ \Omega$ impedance at all parts with control Voltage $V_C = 0 / -5\ \text{V}_{\text{dc}}$, if not otherwise specified)

		min	typ	max	Units
Insertion Loss ($R_{\text{Fin}} - R_{\text{F1or2}}$)	L				dB
1 GHz		-	0.8	-	
6 GHz		-	1	-	
12 GHz		-	1.6	-	
Isolation ($R_{\text{Fin}} - R_{\text{F1or2}}$)	I				dB
1 GHz		-	40	-	
6 GHz		-	32	-	
12 GHz		-	24	-	
Return Loss					dB
1 Hz		-	20	-	
6 GHz		-	15	-	
12 GHz		-	10	-	
Input power at which insertion loss compresses by 1 dB	$P_{\text{in}(-1\text{dB})}$				dBm
0,01 GHz		-	14	-	
0,5 - 12 GHz		-	18	-	
Switching characteristics	t				ns
$t_{\text{rise}}, t_{\text{fall}}$		-	1	-	
$t_{\text{on}}, t_{\text{off}}$		-	2	-	
Control voltages V_C , Leakage Current	c				μA
$V_{\text{CLow}}: 0\ \text{V to } -0,1\ \text{V}$		-	1	-	
$V_{\text{CHigh}}: -5\ \text{V to } -7,5\ \text{V}$		-	80	-	



Insertion Loss


Marker 1	10 MHz
2	450 MHz
3	900 MHz
4	1800 MHz



Return Loss

Isolation

SEMICONDUCTOR DEVICE OUTLINE MW-7



Dim.	Millimeters			Gradient	Remark
	min.	nom.	max.		
A			1,8		
A ₁	0		0,1		
A ₂	1,5	1,6	1,7		
b		0,6			
b ₁	1,62	1,67	1,77		
c	0,24		0,32		
D	6,3		6,7		
E	3,3		3,7		
e ₁		3,81			
e ₂		1,27			
H _E	6,7		7,3		
L _E	0,5				
α				max 15°	1
θ				10°	

1.Applicable on all sides

Terminal identification

- 1 C2
- 2 NC
- 3 RF COM
- 4 C1
- 5 RF2
- 6 GND
- 7 RF1

**Published by Siemens AG, Bereich Bauelemente, Vertrieb,
Produkt-Information, Balanstraße 73, D-8000 München 80.**

© Siemens AG 1991. All Rights Reserved.

As far as patents or other rights of third parties are concerned, liability is only assumed for components per se, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.

Terms of delivery and rights to change design reserved.

For questions on technology, delivery and prices please contact the Offices of Siemens Aktiengesellschaft in the Federal Republic of Germany and Berlin (West) or the Siemens Companies and Representatives worldwide.

Due to technical requirements components may contain dangerous substances. For information on the type in question please contact your nearest Siemens Office, Components Division