

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCR6M00G55-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCR6M00G55-R0

CSTCR6M00G55-R0












Appearance & Shape







Features

MURATA's package technology expertise has enabled the development of the Chip "CERALOCK" with built-in load capacitors. High-density mounting can be realized because of the small package and the elimination of the need for an external load

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. The series is available in a wide frequency range.
- 3. The resonators are extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.



Applications

| Other Usage | Consumer/Industrial |
|-------------|---------------------|
| | |



Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|---------------------|---------------------------------|
| R0 | 180mm Embossed Tape | 3000 |

1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCR6M00G55-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCR6M00G55-R0

CSTCR6M00G55-R0



Specifications

| Draduot Type | Ceramic Resonator | |
|---------------------------|-------------------|--|
| Product Type | (CERALOCK) | |
| Series | CSTCR_G | |
| Frequency | 6.000MHz | |
| Frequency Tolerance | +/-0.50% max. | |
| Operating Temperature | -20°C~80°C | |
| Range | | |
| Frequency Shift by | +/-0.20% max. | |
| Temperature | 7 0.20 % 11.63.11 | |
| Frequency Aging | +/-0.10% max. | |
| Resonant Impedance (R1) | 50ohm max. | |
| Built-in Load Capacitance | 00 5 | |
| (CL1/CL2) | 39pF | |
| Shape | SMD | |
| Wash | Not available | |
| L x W (size) | 4.5x2.0mm | |
| Mass | 29mg | |

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

