

ARM710/ 610

32-bit RISC Processor

OVERVIEW

The new ARM710 32-bit RISC processor delivers industry leading power- and price-performance from a compact package. Capable of sustaining 24 Dhrystone 2.1 MIPS at 28 MHz from a 3.3 V supply, the ARM710 is ideal for cost sensitive high performance applications. The power consumption at 3.3V is just 105 mW (equivalent to 229 MIPS/Watt), which makes the ARM710 by far the best choice for high performance on a tight power budget.

To help the processor maintain high data throughput from inexpensive memory, the ARM710 has an 8kByte cache and a write buffer. A comprehensive Memory Management Unit (MMU) offers full memory

protection facilities, including caching and write buffer control for different areas of memory.

The ARM610 has similar features but with a smaller 4kB cache. Delivering 30 MIPS at 33 MHz from 5V while consuming just half a watt, the ARM610 is ideal when the power budget is not as demanding.

FEATURES

- High performance processor 32-bit RISC
- Very low power consumption
- 3.3 V operation gives even higher performance per watt
- Fully static design-clock can be stopped to save power
- Flexible Memory Management Unit
- Big or little endian addressing


- 8 KByte combined cache
- Write Buffer, so the processor doesn't have to wait for slow memory
- Fast interrupt response time for real-time applications
- Independent processor and memory clocking to accommodate inexpensive memory
- JTAG Boundary Scan Test Interface.

APPLICATIONS

Both the ARM710 and ARM610 are ideal whenever high performance is required within tight cost and power constraints:

- Powerful real-time control
- Hand-held computing
- Portable telecom
- Data communications
- Consumer multi-media
- Automotive control

Block Diagram



SPECIFICATIONS

	ARM710	ARM610
Part number	VY86C710A2	VY86C610C-5
Technology	0.5μM	0.6μM
Die size (mm ² Kmils ²)	34/53	26/41
Transistors	570 295	358 931
Clock frequency	0 to 28 MHz	0 to 33 MHz
Package	144 pin TQFP	144 pin TQFP
Voltage	3.3 ± 10%	5.0 ± 10%
Power consumption	105mW	500mW
MIPS (Dhrystone 2.1)	24	30
MIPS per Watt	229	60
Cache	8K	4K
Write Buffers	8 word, 4 address	8 word, 2 address

All brands, product names, and company names are trademarks or registered trademarks of their respective owners.

With respect to the information in this document, VLSI Technology, Inc. (VLSI) makes no guarantee or warranty of its accuracy or that the use of such information will not infringe upon the intellectual rights of third parties. VLSI shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon it and no patent or other license is implied hereby. This document does not in any way extend or modify VLSI's warranty on any product beyond that set forth in its standard terms and conditions of sale. VLSI reserves the right to make changes in its products and specifications at any time and without notice.

LIFE SUPPORT APPLICATIONS

VLSI's products are not intended for use as critical components in life support appliances, devices, or systems, in which the failure of a VLSI product to perform could be expected to result in personal injury.

For update information, please visit our Web site:
<http://www.vlsi.com>

© 1997 VLSI Technology, Inc. Printed in USA
Document Control: PB-ARM710/610 V1.0 October 97

VLSI 
Technology

VLSI Technology, Inc.
1109 McKay Drive
San Jose, CA 95131