

## SS Coils


Tokin SS Coils are compact and attain large inductance. Thanks to the built-in closed magnetic circuit, they provide effective noise prevention over a wide frequency range.

### Features

- Compact size, large inductance
- Excellent frequency characteristics
- Low magnetic flux leakage

### Applications

- Line filters for switching power supplies
- Eliminates incoming/leaking noise of TV's, VTRs/VCRs and audio equipment
- OA equipment, communications equipment and other electronic devices



Model	Rated Current (A)	Inductance (mH) min.	DC Resistance ( $\Omega$ /line) max.	Dimensions (W x D x H) (mm)
SS10V/H-03330	0.3	33.0	3.2	21 x 16 x 21.5/21 x 21 x 15.5
SS10V/H-04220	0.4	22.0	2.0	21 x 16 x 21.5/21 x 21 x 15.5
SS10V/H-05180	0.5	18.0	1.5	21 x 16 x 21.5/21 x 21 x 15.5
SS10V/H-10039	1.0	3.9	0.36	21 x 16 x 21.5/21 x 21 x 15.5
SS10V/H-15018	1.5	1.8	0.194	21 x 16 x 21.5/21 x 21 x 15.5
SS11V-03550	0.3	55.0	4.1	22 x 14.5 x 21.5
SS11V-04350	0.4	35.00	2.6	22 x 14.5 x 21.5
SS11V-05230	0.5	23.0	1.8	22 x 14.5 x 21.5
SS11V-10062	1.0	6.2	0.44	22 x 14.5 x 21.5
SS11V-17024	1.7	2.4	0.19	22 x 14.5 x 21.5
SS11V-R03820	0.3	82.0	4.1	22 x 14.5 x 21.5
SS11V-R04520	0.4	52.0	2.6	22 x 14.5 x 21.5
SS11V-R05350	0.5	35.0	1.8	22 x 14.5 x 21.5
SS11V-R10093	1.0	9.3	0.44	22 x 14.5 x 21.5
SS11V-R17036	1.7	3.6	0.19	22 x 14.5 x 21.5
SS24H-05350	0.5	35	1.75	26 x 26 x 21
SS24H-07200	0.7	20	1.0	26 x 26 x 21
SS24H-08150	0.8	15	0.75	26 x 26 x 21
SS24H-10100	1.0	10	0.55	26 x 26 x 21
SS24H-15045	1.5	4.5	0.24	26 x 26 x 21
SS24H-18035	1.8	3.5	0.21	26 x 26 x 21
SS24H-20025	2.0	2.5	0.17	26 x 26 x 21
SS24H-R05600	0.5	60	1.75	26 x 26 x 21
SS24H-R07350	0.7	35	1.0	26 x 26 x 21
SS24H-R08250	0.8	25	0.75	26 x 26 x 21
SS24H-R10170	1.0	17	0.55	26 x 26 x 21
SS24H-R15080	1.5	8.0	0.24	26 x 26 x 21
SS24H-R18060	1.8	6.0	0.21	26 x 26 x 21
SS24H-R20045	2.0	4.5	0.17	26 x 26 x 21
SS28V/H-08350	0.8	35	0.95	30 x 22 x 35.5
SS28V/H-10250	1.0	25	0.65	30 x 30 x 24.5
SS28V/H-15100	1.5	10	0.35	30 x 30 x 24.5
SS28V/H-20075	2.0	7.5	0.22	30 x 30 x 24.5
SS28V/H-25045	2.5	4.5	0.16	30 x 30 x 24.5
SS28V/H-R06800	0.8	60	0.95	30 x 30 x 24.5
SS28V/H-R10450	1.0	45	0.65	30 x 30 x 24.5
SS28V/H-R15170	1.5	17	0.35	30 x 30 x 24.5
SS28V/H-R20130	2.0	13	0.22	30 x 30 x 24.5
SS28V/H-R25080	2.5	8.0	0.16	30 x 30 x 24.5
SS35V/15300	1.5	30	0.48	37 x 26.5 x 41
SS35V/20170	2.0	17	0.28	37 x 26.5 x 41
SS35V/25090	2.5	9	0.20	37 x 26.5 x 41
SS35V/30082	3.0	8.2	0.15	37 x 26.5 x 41
SS35V/35047	3.5	4.7	0.10	37 x 26.5 x 41
SS35V/40033	4.0	3.3	0.08	37 x 26.5 x 41
SS35V/45022	4.5	2.2	0.06	37 x 26.5 x 41