

**.110/.125
Quick-Connect Series
In-Line and Flag Type**

— Axial & Closed Back Design —
To Accept .110/.125 x .020
Male Tab

STYLE AND DIMENSIONS	WIRE RANGE	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	22-16	.040-.090	..	10,000	$\frac{1}{8} \pm \frac{1}{32}$.016	Pre Tinned Brass Brass	3650H 2A 3650H 2AB
	22-16	None	..	10,000	$\frac{1}{8} \pm \frac{1}{32}$.016	Pre Tinned Brass Brass	3650H 2A-2 3650H 2AB-2
	22-18	.040-.090	✓✓	10,000	$\frac{7}{32} \pm \frac{1}{32}$.010	Pre Tinned Brass Brass	3650H 102A 3650H 102AB
	22-18	None	✓✓	10,000	$\frac{7}{32} \pm \frac{1}{32}$.010	Pre Tinned Brass Brass	3650H 102A-2 3650H 102AB-2
	24-18	None	..	8000	$\frac{5}{32} \pm \frac{1}{32}$.016	Pre Tinned Brass Brass	3650H 402A 3650H 402AB

* Contact Factory for Latest Agency Approvals.