




Agilent 1N5719, 1N5767, 5082-3001, 5082-3039, 5082-3077, 5082-3080/81, 5082-3188, 5082-3379 PIN Diodes for RF Switching and Attenuating


Data Sheet

Description/Applications

These general purpose switching diodes are intended for low power switching applications such as RF duplexers, antenna switching matrices, digital phase shifters, and time multiplex filters. The 5082-3188 is optimized for VHF/UHF bandswitching.

The RF resistance of a PIN diode is a function of the current flowing in the diode. These current controlled resistors are specified for use in control applications such as variable RF attenuators, automatic gain control circuits, RF modulators, electrically tuned filters, analog phase shifters, and RF limiters.

Outline 15 diodes are available on tape and reel. The tape and reel specification is patterned after RS-296-D.



DIMENSIONS IN MILLIMETERS AND (INCHES).

Outline 15

Features

- Low Harmonic Distortion
- Large Dynamic Range
- Low Series Resistance
- Low Capacitance

Maximum Ratings

Junction Operating and Storage Temperature Range	-65°C to +150°C
Power Dissipation 25°C	250 mW
<i>(Derate linearly to zero at 150°C)</i>	
Peak Inverse Voltage (PIV)	same as V_{BR}
Maximum Soldering Temperature	260°C for 5 sec



Agilent Technologies

Mechanical Specifications

The Agilent Outline 15 package has a glass hermetic seal with dumet leads. The lead finish is 95-5 tin-lead (SnPb) for all PIN

diodes. The leads on the Outline 15 package should be restricted so that the bend starts at least 1/16 inch (1.6 mm) from the glass body. Typical package inductance and capacitance are 2.5 nH and

0.13 pF, respectively. Marking is by digital coding with a cathode band.

General Purpose Diodes

Electrical Specifications at $T_A = 25^\circ\text{C}$

Part Number 5082-	Maximum Total Capacitance C_T (pF)	Minimum Breakdown Voltage V_{BR} (V)	Maximum Residual Series Resistance R_S (Ω)	Effective Carrier Lifetime τ (ns)	Reverse Recovery Time t_{rr} (ns)
General Purpose Switching and Attenuating					
3001	0.25	200	1.0	100 (min.)	100 (typ.)
3039	0.25	150	1.25	100 (min.)	100 (typ.)
1N5719	0.3**	150	1.25	100 (min.)	100 (typ.)
3077	0.3	200	1.5	100 (min.)	100 (typ.)
Band Switching					
3188	1.0*	35	0.6**	70 (typ.)*	12 (typ.)
Test Conditions	$V_R = 50\text{ V}$ * $V_R = 20\text{ V}$ ** $V_R = 100\text{ V}$ $f = 1\text{ MHz}$	$V_R = V_{BR}$ Measure $I_R \leq 10\text{ }\mu\text{A}$	$I_F = 100\text{ mA}$ * $I_F = 20\text{ mA}$ ** $I_F = 10\text{ mA}$ $f = 100\text{ MHz}$	$I_F = 50\text{ mA}$ $I_R = 250\text{ mA}$ * $I_F = 10\text{ mA}$ * $I_R = 6\text{ mA}$	$I_F = 20\text{ mA}$ $V_R = 10\text{ V}$ 90% Recovery

Notes:

Typical CW power switching capability for a shunt switch in a 50 Ω system is 2.5 W.

RF Current Controlled Resistor Diodes

Electrical Specifications at $T_A = 25^\circ\text{C}$

Part Number	Effective Carrier Lifetime t (ns)	Min. Breakdown Voltage V_{BR} (V)	Max. Residual Series Resistance R_S (Ω)	Max. Total Capacitance C_T (pF)	High Resistance Limit, R_H (W)		Low Resistance Limit, R_L (W)		Max. Difference in Resistance vs. Bias Slope, Dc
					Min.	Max.	Min.	Max.	
5082-3080	1300 (typ.)	100	2.5	0.4	1000			8**	
1N5767*	1300 (typ.)	100	2.5	0.4	1000			8**	
5082-3379	1300 (typ.)	50		0.4				8**	
5082-3081	2500 (typ.)	100	3.5	0.4	1500			8**	
Test Conditions	$I_F = 50\text{ mA}$ $I_R = 250\text{ mA}$	$V_R = V_{BR}$ Measure $I_R \leq 10\text{ }\mu\text{A}$	$I_F = 100\text{ mA}$ $f = 100\text{ MHz}$	$V_R = 50\text{ V}$ $f = 1\text{ MHz}$	$I_F = 0.01\text{ mA}$ $f = 100\text{ MHz}$		$I_F = 1.0\text{ mA}$ $I_F = 20\text{ mA}$ ** $f = 100\text{ MHz}$		Batch Matched at $I_F = 0.01\text{ mA}$ and 1.0 mA $f = 100\text{ MHz}$

*The 1N5767 has the additional specifications:

$\tau = 1.0\text{ msec}$ minimum

$I_R = 1\text{ }\mu\text{A}$ maximum at $V_R = 50\text{ V}$

$V_F = 1\text{ V}$ maximum at $I_F = 100\text{ mA}$.

Typical Parameters at $T_A = 25^\circ\text{C}$ (unless otherwise noted)




Figure 1. Forward Current vs. Forward Voltage.




Figure 2. Typical RF Resistance vs. Forward Bias Current.




Figure 3. Typical RF Resistance vs. Forward Bias Current.




Figure 4. Typical Capacitance vs. Reverse Voltage.




Figure 5. Typical Capacitance vs. Reverse Voltage.




Figure 6. Typical Reverse Recovery Time vs. Forward Current for Various Reverse Driving Voltages.




Figure 7. Typical Second Order Intermodulation Distortion.




Figure 8. Typical Cross Intermodulation Distortion.

Diode Package Marking

1N5xxx 5082-xxxx

would be marked:

1Nx xx

xxx xx

YWW YWW

where xxxx are the last four digits of the 1Nxxxx or the 5082-xxxx part number. Y is the last digit of the calendar year. WW is the work week of manufacture.

Examples of diodes manufactured during workweek 45 of 1999:

1N5712 5082-3080

would be marked:

1N5 30

712 80

945 945

Part Number Ordering Information

Part Number	No. of devices	Container
5082-3xxx#T25/1N57xx#T25	2500	Tape & Reel
5082-3xxx#T50/ 1N57xx#T50	5000	Tape & Reel
5082-3xxx/ 1N57xx	100	Antistatic bag

www.agilent.com/semiconductors

For product information and a complete list of distributors, please go to our web site.

For technical assistance call:

Americas/Canada: +1 (800) 235-0312 or
(916) 788-6763

Europe: +49 (0) 6441 92460

China: 10800 650 0017

Hong Kong: (+65) 6756 2394

India, Australia, New Zealand: (+65) 6755 1939

Japan: (+81 3) 3335-8152(Domestic/International), or
0120-61-1280(Domestic Only)

Korea: (+65) 6755 1989

Singapore, Malaysia, Vietnam, Thailand, Philippines,
Indonesia: (+65) 6755 2044

Taiwan: (+65) 6755 1843

Data subject to change.

Copyright © 1999-2005 Agilent Technologies, Inc.

Obsoletes 5968-7182E

June 20, 2005

5989-3339EN



Agilent Technologies