


Hutton Close, Crowther Ind Est, Washington, Tyne & Wear NE38 0AH, England
<mailto:sales@isocom.uk.com> - Tel: +44 (0)191 4166546 - Fax: +44 (0)191 4155055

Triac Couplers Single Channel DIP, Light Activated

[Optocouplers Catalogue](#)
[Home Page](#)



PARAMETER	CONDITION	VALUE
Continuous Forward Current	Max	60mA
PIV LED	10mA	Min 3V
Peak Off-State Reverse Current	Vdrm=Rated	Max 100nA

Parameter	Input Trigger Current, Max	Isolation Breakdown Voltage RMS	Peak Blocking Voltage
Condition	Vtm=3V RI=150ohm		
H11J1	10 mA	3600 V	250 V
H11J2	15 mA		
H11J3	10 mA	2500 V	
H11J4	15 mA		
H11J5	25 mA		
IS3020	30 mA	2500 V	400 V
IS3021	15 mA		
IS3022	10 mA		
IS3023	5 mA		
IS3024	3.5 mA		
IS607	10 mA	4000 V	450 V
IS608	7 mA		
MOC3009	30 mA	7500 V	250 V
MOC3010	15 mA		
MOC3011	10 mA		
MOC3012	5 mA		

MOC3022	10 mA	400V
MOC3023	5 mA	

With same circuit: [IS3051](#), [IS3052](#)

[Contents](#)