

		DESIGNED FOR USE WITH OSS SR CABLE ENTRY DIAMETER MINIMUM		REVISIONS																																												
		HOUSING .0875 CONTACT .0234		REV 01	DESCRIPTION REVISED	DATE 8/15/88	APPROVED [Signature]																																									
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr><tr><td>Nominal Impedance (Ohms) 50 Frequency Range (GHz) D.C. TO 26.0 Volt Rating (VRMS MAX) 250 VSWR 1.15 +.015 (GHz) Insertion Loss .04 V/GHz RF Leakage -60 dB MIN @ 6.0 TO 8.0 GHz Corona, 70,000 Ft (VRMS MIN) 190 Dielectric Withstanding Voltage (VRMS MIN) 750 Contact Resistance (Milliohms MAX) Center Contact 4.0 Outer Contact 2.0 Cable To Housing (Milliohms MAX) 0.5 RF High Potential (VRMS MIN @ 5 MHz) 500 IR (Megohms) 5000</td><td>Interface Dimensions MIL-STD-348 FIG. 319-1 Recommended Mating Torque 7-8 IN-POUNDS Mating Characteristics: Insertion (MAX Lbs) N/A Withdrawal (MIN Oz) N/A Connector Engagement and Disengagement (In/Lbs MAX) 2.0 Center Contact Captivation Axial 6.0 LBS MIN Radial 4.0 IN-OUNCES Cable Retention Axial Force 30 LBS Torque 16 IN-OUNCES MIN Weight (Grams) 2.0</td><td>Temperature Rating -65°C to 165°C Vibration - MIL-STD-202, Method 204, Condition D Shock - MIL-STD-202, Method 213, Condition I Thermal shock MIL-STD-202, Method 107 Test Condition B Except High Temp 115°C Moisture Resistance - MIL-STD-202, Method 106 Corrosion - MIL-STD-202, Method 101, Condition B .XXX = In XX.X = mm (REF)</td></tr></table>		ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50 Frequency Range (GHz) D.C. TO 26.0 Volt Rating (VRMS MAX) 250 VSWR 1.15 +.015 (GHz) Insertion Loss .04 V/GHz RF Leakage -60 dB MIN @ 6.0 TO 8.0 GHz Corona, 70,000 Ft (VRMS MIN) 190 Dielectric Withstanding Voltage (VRMS MIN) 750 Contact Resistance (Milliohms MAX) Center Contact 4.0 Outer Contact 2.0 Cable To Housing (Milliohms MAX) 0.5 RF High Potential (VRMS MIN @ 5 MHz) 500 IR (Megohms) 5000	Interface Dimensions MIL-STD-348 FIG. 319-1 Recommended Mating Torque 7-8 IN-POUNDS Mating Characteristics: Insertion (MAX Lbs) N/A Withdrawal (MIN Oz) N/A Connector Engagement and Disengagement (In/Lbs MAX) 2.0 Center Contact Captivation Axial 6.0 LBS MIN Radial 4.0 IN-OUNCES Cable Retention Axial Force 30 LBS Torque 16 IN-OUNCES MIN Weight (Grams) 2.0	Temperature Rating -65°C to 165°C Vibration - MIL-STD-202, Method 204, Condition D Shock - MIL-STD-202, Method 213, Condition I Thermal shock MIL-STD-202, Method 107 Test Condition B Except High Temp 115°C Moisture Resistance - MIL-STD-202, Method 106 Corrosion - MIL-STD-202, Method 101, Condition B .XXX = In XX.X = mm (REF)	<table><tr><th>COMPONENT</th><th>MATERIAL</th><th>FINISH</th></tr><tr><td>HOUSING CAP</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>COUPLING NUT</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303</td><td>PASSIVATE PER OO-P-35</td></tr><tr><td>DIELECTRIC</td><td>TFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>RETAINING RING</td><td>BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H</td><td>N/A</td></tr><tr><td>GASKET</td><td>SILICONE RUBBER PER ZZ-R-765</td><td>N/A</td></tr></table>		COMPONENT	MATERIAL	FINISH	HOUSING CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204	COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER OO-P-35	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A	GASKET	SILICONE RUBBER PER ZZ-R-765	N/A	<table><tr><td>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC DEC ANGLES + .005 + .005 + .005</td><td>DATE 12/88 CHECKED BY BB 4/15/88 APPROVED BY MCD 4/18/88</td><td> an AMP company</td><td>M/A-COM, Inc. Waltham, MA 02254</td></tr><tr><td colspan="2">USE ASSY PROCEDURE NO AP 10-054</td><td colspan="2">TITLE OSSM RIGHT ANGLE CABLE PLUG DIRECT SOLDER ATTACHMENT</td></tr><tr><td>SIZE B</td><td>CODE IDENT NO 26805</td><td>1007-5015-92</td><td>REV 01</td></tr><tr><td colspan="2">SCALE 5:1</td><td colspan="2">SHEET 1 OF 1</td></tr></table>		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC DEC ANGLES + .005 + .005 + .005	DATE 12/88 CHECKED BY BB 4/15/88 APPROVED BY MCD 4/18/88	 an AMP company	M/A-COM, Inc. Waltham, MA 02254	USE ASSY PROCEDURE NO AP 10-054		TITLE OSSM RIGHT ANGLE CABLE PLUG DIRECT SOLDER ATTACHMENT		SIZE B	CODE IDENT NO 26805	1007-5015-92	REV 01	SCALE 5:1		SHEET 1 OF 1	
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																														
Nominal Impedance (Ohms) 50 Frequency Range (GHz) D.C. TO 26.0 Volt Rating (VRMS MAX) 250 VSWR 1.15 +.015 (GHz) Insertion Loss .04 V/GHz RF Leakage -60 dB MIN @ 6.0 TO 8.0 GHz Corona, 70,000 Ft (VRMS MIN) 190 Dielectric Withstanding Voltage (VRMS MIN) 750 Contact Resistance (Milliohms MAX) Center Contact 4.0 Outer Contact 2.0 Cable To Housing (Milliohms MAX) 0.5 RF High Potential (VRMS MIN @ 5 MHz) 500 IR (Megohms) 5000	Interface Dimensions MIL-STD-348 FIG. 319-1 Recommended Mating Torque 7-8 IN-POUNDS Mating Characteristics: Insertion (MAX Lbs) N/A Withdrawal (MIN Oz) N/A Connector Engagement and Disengagement (In/Lbs MAX) 2.0 Center Contact Captivation Axial 6.0 LBS MIN Radial 4.0 IN-OUNCES Cable Retention Axial Force 30 LBS Torque 16 IN-OUNCES MIN Weight (Grams) 2.0	Temperature Rating -65°C to 165°C Vibration - MIL-STD-202, Method 204, Condition D Shock - MIL-STD-202, Method 213, Condition I Thermal shock MIL-STD-202, Method 107 Test Condition B Except High Temp 115°C Moisture Resistance - MIL-STD-202, Method 106 Corrosion - MIL-STD-202, Method 101, Condition B .XXX = In XX.X = mm (REF)																																														
COMPONENT	MATERIAL	FINISH																																														
HOUSING CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204																																														
COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER OO-P-35																																														
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A																																														
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																														
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A																																														
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A																																														
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC DEC ANGLES + .005 + .005 + .005	DATE 12/88 CHECKED BY BB 4/15/88 APPROVED BY MCD 4/18/88	 an AMP company	M/A-COM, Inc. Waltham, MA 02254																																													
USE ASSY PROCEDURE NO AP 10-054		TITLE OSSM RIGHT ANGLE CABLE PLUG DIRECT SOLDER ATTACHMENT																																														
SIZE B	CODE IDENT NO 26805	1007-5015-92	REV 01																																													
SCALE 5:1		SHEET 1 OF 1																																														

COPY IN PUERTO RICO

CUSTOMER

Tyco PART #1045418
SHEET 1 of 1 REV 0