



SD

3152-4-5

STAMP: KINGS 3152-4-5
YRWK (DATE CODE)
(SEE NOTE 5)

M29 x 1.5 MM THREAD

NOTES:

1. FOR USE WITH ANDREW FSJ4-50B AND FSJ4RN-50B CABLE. (1/2 IN. HELIAX)
2. INTERFACE PER, IEC STANDARD 169-4 (TYPE 7-16 MM).
3. FOR CABLE INSTRUCTIONS SEE 3-654-2.
- 3A. FOR CABLE OUTER CONDUCTOR FLARING USE KTH-9000.
4. MATERIALS:
CENTER CONTACT: BERYLLIUM COPPER.
O RINGS & GASKET: SILICONE RUBBER.
INSULATOR: TEFLON.
CAP PROTECTIVE: VINYL.
ALL OTHER METAL PARTS: BRASS.
5. FINISHES:
CENTER CONTACT: SILVER PLATE.
ALL OTHER METAL PARTS: KINGS TARNISH RESISTANT WHITE BRONZE ALLOY (TR3) OR SILVER PLATE.
FOR SILVER PLATE, ORDER PART NUMBER AS SHOWN. FOR WHITE BRONZE PLATING,
ADD "MJ3" SUFFIX TO THE PART NUMBER SHOWN, FOR EXAMPLE 3152-4-5 MJ3.
6. ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS.
FREQUENCY RANGE: DC TO 6.0 GHz.
OPERATING VOLTAGE: 2700 VRMS.

REVISIONS

ISSUE	CHANGES
0	ER 38187 HVN 01/22/01
1	CN 38377 A HVN 08/14/01
2	CN 38442 E TML 12/05/01

3252-4-5S

SCALE 3:1

APPROX SURFACE AREA

WAS: E-19251C

USED ON

REF:

7/16, PNL ANG, F.

DRAWN HVN DATE 03/05/01

DESIGN LJ DATE 10/20/97

APPR. DATE

KINGS
ELECTRONICS CO., INC.
ROCK HILL, SOUTH CAROLINA 29730

3152-4-5

SD