

**.300 Ring
Insulation Piercing — 2 Barbs**

**Spade and Ring Series
Uninsulated**

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
4	.050-.070	— —	4000	—	.020	Brass	3H1-4-2	
						Pre Tinned Brass	3H2-4-2	
	.075-.125	— —	4000	—	.020	Brass	3H1-4	
						Pre Tinned Brass	3H2-4	
.130	.050-.070	— —	4000	—	.020	Brass	3H1-6A-2	
						Pre Tinned Brass	3H2-6-2	
6	.050-.070	— —	4000	—	.020	Brass	3H1-6-2	
						Pre Tinned Brass	3H2-6-2	
	.075-.125	— —	4000	—	.020	Brass	3H1-6	
						Pre Tinned Brass	3H2-6	
8	.050-.070	— —	4000	—	.020	Brass	3H1-8-2	
						Pre Tinned Brass	3H2-8-2	
	.075-.125	— —	4000	—	.020	Brass	3H1-8	
						Pre Tinned Brass	3H2-8	
10	.050-.070	— —	4000	—	.020	Brass	3H1-10-2	
						Pre Tinned Brass	3H2-10-2	
	.075-.125	— —	4000	—	.020	Brass	3H1-10	
						Pre Tinned Brass	3H2-10	

**.300 Hook
20-14 AWG**

**Spade and Ring Series
Uninsulated**

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
6	.075-.175	✓ ✓	5000	$5/32 \pm 1/32$.020	Brass	A3H1-6	
						Pre Tinned Brass	A3H2-6	
8	.075-.175	✓ ✓	5000	$5/32 \pm 1/32$.020	Brass	A3H1-8	
						Pre Tinned Brass	A3H2-8	
6	None	✓ ✓	5000	$5/32 \pm 1/32$.020	Brass	A3H1-5	
						Pre Tinned Brass	A3H2-5	
8	None	✓ ✓	5000	$5/32 \pm 1/32$.020	Brass	A3H1-7	
						Pre Tinned Brass	A3H2-7	