REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE



RECOMMENDED
CABLE STRIPPING DIM'S







NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
3. PHOSPHOR BRONZE PER QQ-B-750
4. GOLD PL. 3 MIN THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
5. JIS H 3250, C 2700

1. CRIMPED FERRULE
HEX CRIMP SIZE .255"
2. CRIMPED CONTACT PIN
HEX CRIMP SIZE .068"

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
6	FERRULE	NOTE 5	NOTE 2	1	FR-75/66X127
5	CONTACT PIN	NOTE 3	NOTE 4	1	B74000-8-25/076
4	BARREL	NOTE 1	NOTE 2	1	B50900-6-56/39
3	INSULATOR	DELRIN	NATURAL	1	B74050-3-75-B
2	BODY	NOTE 1	NOTE 2	1	T74000-2
1	HOUSING	NOTE 1	NOTE 2	1	B75000-1

DIMENSIONS ARE IN MILLIMETERS

UNLESS OTHERWISE SPECIFIED TOLERANCES
0.5-6 = ±0.2
6-30 = ±0.4
30-120 = ±0.6
120-315 = ±1
315-1000 = ±1.6
1000-2000 = ±2.4

SCALE 2 5/1 | ISSUE A

PART NO. T6521A1-ND3G-3-75

APPROVED DATE 10-11-01'

CHECKED DATE 10-11-01'

DRAWN DATE 10-11-01'

FILE NO.

Amphenol

TITLE
TNC PANEL CRIMP JACK

DRAWING NO.
KJ-T6521A1-ND3G-59U-75

ITEM NO.