Amphenol Nexus Technologies, Incorporated

50 Sunnyside Ave. Stamford, CT 06902

Phone: 203-327-7300 • Fax: 203-324-7623

Email: salesinfo@nexus.com • Website: www.nexus.com



Item # AP-107DRS, Plug, Shielded

$\underline{Specifications} \quad \underline{Features} \quad \underline{Options} \quad \underline{Applications}$

Specifications

Specifications	
Conductors	7
Application	Ruggedized Commercial / Military
Contact Types	Insulation Piercing
Rear Accessory	Overmold Cap
Shell Material	Aluminum
Plating Material	Black Anodize (standard) Black Chrome (shielded)
Insert Material	Thermoset Plastic
Contact Material	Gold-plated BeCu
Mating	Axial Push-Pull Motion
Engagement Force	≤ 14 lb
Disengagement Force	8 to 12 lb
Mating Cycles	5000
Temperature	-55 to 85 °C
Contact Current Capacity	3 A
Contact Resistance	≤ 150 mV

Features

- Plug and Jack breakaway connectors designed to function in severe environments
- Watertight in up to 6 feet of water
- Molded-in wiping-action contacts provide self-cleaning feature and eliminate issues with pin/socket open contacts
- Designed for multiple cable diameters
- Miniature versions are 50% smaller than standard connectors while maintaining many of the same performance characteristics

Options

- 7- or 10-pin (miniature version only) contacts
- Solder-type contacts or insulation-piercing contacts
- Wire strain relief or over-molded versions available for all plugs and jacks
- Panel mount versions are available for both front- and rear-mount panels
- Shielding is available in all connector choices
- All standard connector options also available in miniaturized versions

Applications

- C4I Systems
- Military Vehicles
- Commercial Aircraft
- Telecommunications Equipment
- Missiles and Ordnance
- Medical Equipment
- Commercial / Industrial Equipment

Amphenol Nexus Technologies, Incorporated

50 Sunnyside Ave. Stamford, CT 06902

Phone: 203-327-7300 • Fax: 203-324-7623

Email: salesinfo@nexus.com • Website: www.nexus.com