

# EB-25/26/27

## Terminal Blocks

### APPLICATION

The EB-25, -26, and -27 line of terminal blocks are used where any permanent or temporary wiring connections are required especially if many wires are involved.

### DESCRIPTION

The EB-25, -26, and -27 terminal blocks are molded one piece design available in 4, 6, and 12 points.

They are furnished with washer-less head binding screws (#10-32) for circuit wire connections. The blocks are supplied with a black marking strip with white numbers on one side, and white unmarked on the reverse side for circuit identification. To mount the terminal block, drill for a No. 10 screw. The board will accommodate No. 18 to No. 10 inclusive wire sizes.

The EB-26 is of the same construction and dimensions as the type EB-25, except the clamp type connections are furnished for circuit wire connections. The board will accept wire sizes No.18 to No.10 inclusive.

The EB-27 terminal block is the same as the type EB-25, except that short circuit strips are supplied in lieu of a marking strip.

On the EB-25, EB-26, and EB-27 terminal blocks, the minimum spacing between the barrier separation is 11/32 inches.

The distance between adjacent connection screws is 5/8 inches.

- UL Listed

### Selection Guide

No. of Circuits	Catalog Number Without Cover	Catalog Number With Cover
<b>EB-25 with Washer-Head Screws</b>		
4	EB25B04	EB25B04C
6	EB25B06	EB25B06C
12	EB25B12	EB25B12C
<b>EB-26 with Pressure Type Connectors</b>		
4	EB26B04	EB26B04C
6	EB26B06	EB26B06C
12	EB26B12	EB26B12C
<b>EB-27 with Washer-Head and Short-Circuit Strips (No Marking Strip)</b>		
4	EB27B04S	EB27B04SC
6	EB27B06S	EB27B06SC
12	EB27B12S	EB27B12SC

### Dimensions

