

NV11M09YA

Voltage Controlled Crystal Oscillator (VCXO)

Main Application

For , SDH-, and SONET-related equipment.

Features

- Frequency range : 75 to 800MHz. A wide frequency band. (PECL)
- Fundamental crystal units are designed.(Frequency Multiplying Model from 210MHz)
- Low jitter(Max. 1ps)
- Enable/Disable function is optional.
- Low power supply voltage(+3.3 V)

Pb Free

RoHS Compliant
Directive 2011/65/EU



Specifications


Item	Model	NV11M09YA
Nominal Frequency Range (MHz)		75 to 800
Supply Voltage [V _{CC}] (V)		+3.3V±10%
Control Voltage [V _{cont}] (V)		+1.65±1.5
Current Consumption (mA)		Max. 65
Output Voltage		V _{OH} : Min. V _{CC} -1.02 V, V _{OL} : Max. V _{CC} -1.60 V
Symmetry (%)		45 to 55 (at 50% V _{out})
Rise Time / Decay (Fall) Time		Max. 1ns(20% to 80%)
Output Load Condition (TTL)		50Ω(V _{CC} -2V)
Operating Temperature Range (°C)		-40 to +85
Storage Temperature Range (°C)		-55 to +125
Overall Frequency Tolerance (*)		Max. ±50×10 ⁻⁶
Frequency Control Range		Min. ±100×10 ⁻⁶
Frequency Change Polarity		Positive
Linearity of Frequency Modulation Deviation		Max. 5%
Input Impedance		Min. 100kΩ
Phase Jitter		Max. 1ps (12kHz to 20MHz)

(*) Overall frequency tolerance includes "Frequency/temperature characteristics", "Frequency tolerance", "Frequency/voltage coefficient", "Frequency/load coefficient" and "Long-term frequency stability(1 year)".

* Please specify products with or without Enable/Disable function.

* Please do not reflow the board upside down after mounting this product. (The product itself or the cover may fall off.)

Dimensions



List of Enable / Disable function

Input (#2)
Low (V _{IL} ≤ V _{CC} -1.5V) or NC
High (V _{IH} ≥ V _{CC} -1.1V)

Output (#4, #5)
Nominal frequency Output
High Z

Specification Number

Frequency (MHz)	Specification Number	
	Without Enable/Disable function	With Enable/Disable function
100	NSA3532A	NSA3532C
106.25		
122.88		
125		
155.52		
156.25		
160		
167.3316		
184.32		
200		
245.76	NSA3532B	NSA3532D
320		
368.64		
491.52		
622.08		
640		
644.5313		
666.5143		
669.3266		
672.1627		
693.483		
696.4215		
698.8123		
764.4203		
777.6		
792.0087		
794.728		
800		

Please specify the model name, frequency, and specification number when you order products. For further questions regarding specifications, please feel free to contact us.