

Color-Keyed®

Connectors for Copper Conductor



COMPRESSION



Copper Two-Way Splicers for up to 600V to 35KV Application

Cat. No.	Cable+ Size	Dimensions (in.)		Installing Tools		
				13100A, TBM151* & TBM14M		
				Die Set Cat. No.	Color Code	Strip Length (in.)
54006	#4 AWG	2.00	.37	15CA29R	Gray	1½
54007	#2 AWG	2.13	.41	15CA33R	Brown	1½
54008	#1 AWG	2.25	.47	15CA37R	Green	1½
54009	1/0 AWG	2.38	.52	15CA42R	Pink	1¾
54010	2/0 AWG	2.38	.57	15CA45R	Black	1¾
54011	3/0 AWG	2.63	.63	15CA49R	Orange	1¾
54012	4/0 AWG	2.69	.69	15CA54R	Purple	1¾
54013	250 kcmil	3.19	.74	15CA60R	Ruby	2½
54015	350 kcmil	4.13	.89	15CA71R	Red	2¾
54018	500 kcmil	4.13	1.06	15CA87R	Brown	2¾
54023	750 kcmil	4.75	1.30	15CA106R	Black	

* Cat. No. 15500-TB Die Adaptor required for TBM151

+ Cable Size: Concentric and Compact strandings

Tooling: Pg. 79-100

Die Selector Chart: Pg. 105-109

