



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. TEFLON MIL-P-19468
 5. JIS H 3250, C 2700

8	COVER	NOTE 1	NOTE 2	1	CV-7X1-T
7	FERRULE	NOTE 5	NOTE 2	1	FR-75/66X127
6	CONTACT PIN	NOTE 1	NOTE 3	1	MU1112A3-6
5	SHELL	NOTE 1	NOTE 2	1	PT-4000-002-1
4	RETAINER RING	SUS 304	NATURAL	1	PT-4000-002-6-B
3	INSULATOR	NOTE 4	NATURAL	1	RFU-600-10C1-7
2	BODY	NOTE 1	NOTE 2	1	MU1112A1-2
1	BARREL	NOTE 1	NOTE 2	1	MU1112A3-1-56/42
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS
 UNLESS OTHERWISE SPECIFIED TOLERANCES
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

PART NO.	MU1112A3-NT3G-7B-50
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'
FILE NO.	

Amphenol	
TITLE MINI-UHF R/A CRIMP PLUG (FOR BELDEN RG-8/X, TIMES LMR-240MA)	
DRAWING NO. KJ-MU1112A3-NT3G-8X-50	
ITEM NO.	