

ELECTRICAL SPECIFICATIONS:
 VOLTAGE RATING: AC 500V
 WITH STANDING VOLTAGE: AC 1,500V ONE MINUTE
 INSULATION RESISTANCE: ~~1000M~~ 1000M AT DC 500V
 CONTACT RESISTANCE: 3MW MAX AT DC 1A
 FREQUENCY RANGE: 0-4GHZ
 VSWR: 1.2 MAX 0-2GHZ
 IMPEDANCE: 50 OHM VERSIONS

BNC-PC-58-LF
 LEADFREE

RoHS Compliant

9	FERRULE	BRASS	NICKEL	1
8	GASKET	RUBBER	RED	1
7	WASHER	STEEL	NICKEL	1
6	SPRING	SK-5	NICKEL	1
5	WASHER	STEEL	NICKEL	1
4	PIN	BRASS	GOLD	1
3	INSULATOR	DELRIN	WHITE	1
2	BODY	BRASS	NICKEL	1
1	SHELL	BRASS	NICKEL	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY

MORETHANALL
 CONNECTORS
 ASSEMBLIES

PART NO. BNC-PC-58

DWG NO. BNC-PC-58

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



UNLESS OTHERWISE SPECIFIED
 TOLERANCES
 0.5-5 =±0.2
 6-30 =±0.4
 30-120 =±0.6
 120-315 =±1
 315-1000 =±1.6
 1000-2000 =±2.4

DESCRIPTION: BNC MALE CRIMP

AREA

REVISIONS

HK

DATE

焜倫股份有限公司