



**— Axial Bridge Design —
To Accept .187 x .032 Male Tab**



**.187 Quick-Connect Series
Fully Insulated Insul-Connect®
In-Line Type**

WIRE RANGE	MAX. INSUL. DIAMETER "A"	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
22-18	.160	* *	2800	$7/32 \pm 1/32$.016	Pre Tinned Brass	3500P6A	
	.210	* *					3500P7A	
16-14	.160	* *	2800	$7/32 \pm 1/32$.016	Pre Tinned Brass	3500 P8A	
	.210	* *					3500 P9A	

* Contact Factory for Latest Agency Approvals

**To Accept .187 x .020
Female Quick-Connect**

**.187 Quick-Connect Series
Pre-Insulated Male In-Line Type**

WIRE RANGE	MAX. INSUL. DIAM. "A"	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
22-18	.117 .147	✓ ✓ ✓ ✓	4000	$9/32 \pm 1/32$.020	Pre Tinned Brass	50968	
						Brass	50967	
						Pre Tinned Brass	50968-8	
						Brass	50967-8	
16-14	.147 .200	✓ ✓ ✓ ✓	4000	$9/32 \pm 1/32$.020	Pre Tinned Brass	50970	
						Brass	50969	
						Pre Tinned Brass	50970-8	
						Brass	50969-8	