



NOTES:

1. MATERIALS:
ALL METAL PARTS: BRASS PER ASTM B16
INSULATOR: TEFLON PER ASTM D1710
2. FINISH:
BODY: .000015 MIN. GOLD PER MIL-G-45204 OVER .000050
MIN. NICKEL PER QQ-N-290
CONTACT: .000030 MIN. GOLD PER MIL-G-45204 OVER .000050
MIN. NICKEL PER QQ-N-290
END CAP: .000005 MIN. GOLD PER MIL-G-45204 OVER .000050
MIN. NICKEL PER QQ-N-290
3. FOR USE WITH .141 SEMI-RIGID OR EQUIVALENT CABLE.
4. FOR CABLING USE CAP 5-05 WITH ABOVE TRIMMING DIMENSIONS.

THIS INFORMATION IS PROPRIETARY AND CONFIDENTIAL. IT IS DISCLOSED TO YOU ON CONDITION NO FURTHER DISCLOSURE IS MADE TO OTHER THAN RETCONN PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM RETCONN INC., TORRINGTON, CT.

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE NOMINAL AND
FOR REFERENCE ONLY.
DIMENSIONS IN INCHES
DO NOT SCALE PRINT

SALES DRAWING



RETCONN
A SUBSIDIARY OF SPM
199 W. PEARL ROAD TORRINGTON, CT. 06790
TEL (860) 489-1220 FAX (860) 496-7307

TITLE					
SMB RIGHT ANGLE JACK					
DRAWN	DATE	CHECKED	SCALE	FSCM OD	
KJT	5/5/98	<i>gmaled</i>	6:1		
APPR.	DWG. NO.				REV.
<i>RJP</i>	513-500-1410H				

REV.	DESCRIPTION OF CHANGE	DATE	DRN	APPR	MATERIAL
-	RELEASED PER NPR 833	5/5/98	KJT	<i>RJP</i>	
REVISIONS					
FINISH					