

PRODUCT-DETAILS

ACS355-01E-04A7-2

ACS355-01E-04A7-2 Pn 0,75kW, I2n 4,7A IP20.



General Information

Global Commercial Alias	ACS355-01E-04A7-2
Product ID	3AUA0000058167
ABB Type Designation	ACS355-01E-04A7-2
EAN	6438177223429
Catalog Description	ACS355-01E-04A7-2 Pn 0,75kW, I2n 4,7A IP20.
Long Description	<p>The ACS355 drives are designed to meet the requirements of an extensive range of machinery applications in food and beverage, material handling, lifting, textile, printing, rubber and plastics, and woodworking applications.</p> <p>The drive is user-friendly, yet it provides a wide range of built-in technology such as the safe torque off functionality and sequence programming, reducing the need for additional control electronics. The product offers options and diverse functionality to cater to the needs set for speed and torque control of AC induction and permanent magnet motors.</p>

Ordering

Country of Origin	China (CN)
Customs Tariff Number	85044084
Invoice Description	ACS355-01E-04A7-2 Pn 0,75kW, I2n 4,7A IP20.
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	1.8 kg
Product Net Depth / Length	161 mm
Product Net Height	239 mm
Product Net Length	161 mm
Product Net Width	70 mm
Package Level 1 Depth / Length	344 mm
Package Level 1 Height	132 mm
Package Level 1 Width	217 mm
Package Level 1 Units	1 carton

Technical

Number of Phases	1
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Frequency (f)	50/60 Hz
Input Voltage (U_{in})	200 ... 240 V
Mounting Type	Module for cabinet building
Communication Protocol	MODBUS LON DeviceNet PROFIBUS CAN EtherNet/IP PROFINET IO TCP/IP Other Bus Systems
Number of Hardware Interfaces	Industrial Ethernet 0 PROFINET 0 RS-232 1 RS-422 0 RS-485 1 Serial TTY 0 USB 0 Parallel 0 Other 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	1
Number of Digital In/Outputs	5/1
Output Current, Normal Use	4.7 A
Output Power, Light-Overload Use	0.75 kW
Output Power, Normal Use	0.75 kW
Ecodesign Exemption	Energy efficiency data is not provided for the 1~230 V drives. The drives with one phase input are not in the scope of the EU ecodesign requirements (Regulation EU/2019/1781).

Additional Information

Product Main Type	ACS355
Product Name	Frequency converter

Classifications

Product Series	ACS355
ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Environmental

SCIP	4ba0f6ae-3da2-4d0e-9737-b05ac07cf044 Finland (FI)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Where Used (as part of "kit")

Identifier	Description	Type
3AUA0000157173	ACS355-01E-04A7-2 Solar Pump Drive; ACS355-01E-04A7-2 Pn 0,37kW, I2n 4,7A IP20 Solar Pump Drive	Kit

Categories

Drives → Low Voltage AC Drives → Machinery Drives → ACS355 - Machinery Drive

