



PUSHBUTTON

HOME > PRODUCTS > SWITCHES > PUSHBUTTON > PRODUCT DETAILS

EP11SD1ABE EP SERIES SEALED TINY PUSHBUTTON SWITCHES



The EP series of sealed tiny pushbutton switches from C&K are selected to power applications in the telecommunications and networking industry. The EP's snap-fitting actuator accepts standard caps, and is sealed to protect against solder and cleaning processes – helping ensure it can withstand any harsh environment. Available in thru-hole and surface mount models, C&K's EP switches are also RoHS compliant.

FEATURES AND BENEFITS

- Snap-fitting actuator accepts standard caps
- Sealed against solder & cleaning processes
- Thru-hole and surface mount models

TYPICAL APPLICATIONS

- Telecommunications & networking equipment
- Instrumentation & controls
- Computers & peripherals

Image shown represents the product series and may not indicate the actual part number


TOOLBOX

[Product Selection Guide](#)
[Sales Locator](#)

DOWNLOADS

[Datasheet](#)
[Complete Product Line](#)

SPECIFICATIONS

Contact Rating:	Gold contact material: 0.4 VA max. @ 20 V AC or DC max. See datasheet for additional ratings
Contact Resistance:	Below 20 milliohms typ. initial @ 2-4 V DC, 100 mA, for both silver and gold plated contacts
Electrical Life:	EP11, EP21 models: 60,000 make-and-break cycles at full load. EP12 models: 30,000 cycles
Solderability:	Per MIL-STD-202F method 208D, or EIA RS-186E method 9 (1 hour steam aging)
Dielectric Strength:	1,000 Vrms min. @ sea level
Insulation Resistance:	10 ⁹ ohms min.
Operating Temperature:	-30°C to 85°C
Certifications:	 models available

EP11SD1ABE

Most Common:	Yes
Current Rating:	0.4VA (AC/DC)
Circuit:	SPST-NO
Mounting Type:	Thru-hole, Right Angle
Sealing:	Sealed - IP57
Illumination:	None
Switch Function:	Off-Mom
Electrical Life Cycles:	60,000
Voltage Rating - AC:	20V
Voltage Rating - DC:	20V
Actuator Type:	Round, Plunger
Color - Actuator/Cap:	Black

CONTACT TECH SUPPORT

SEARCH DISTRIBUTOR STOCK

REQUEST SAMPLE

3D MODEL

Illumination Type, Color:

**Illumination Voltage
(Nominal):**

Termination Style: Surface Mount, Right Angle

Additional Features: Epoxy Sealed Terminals

Panel Cutout Dimensions:

Packaging: Tray



[Sitemap](#)

[Terms & Conditions](#)

[Legal](#)

[Privacy](#)

[Careers](#)

[Contact Sales](#)

