

Note s:

1.Nominal voltage: 300V/8A

PITCH:3.5mm

2. Insulation Withstands Voltage:

AC1600V/MIN

3. Insulation Resistance:

1000M Ω or more at DC500V

4.Using temperature range:-40C°~115C°

5.Soldering temperature range:260C°±5C°/10sec

Undimensioned Tolerances:

$$\text{Dim.L} = (P-1) \times 3.5 + 4.2$$
$$\text{Dim. B} = (P-1) \times 3.5$$

P = number of poles

	Dim B	Dim L
0-30mm	±0.15	±0.20
over 30mm-60mm	±0.20	±0.25
over 60mm-90mm	±0.25	±0.30
over 90mm	±0.30	±0.40

3	PIN	COPER	TIN PLATED	P
2	Light guide	PC UL94V-0		P
1	BODY	PA6T UL94V-0	BLACK	1
ITEM	NAME OF PART	MATERIAL	NOTES	Q"TY

RoHS compliant
Unit: mm

Scale	Free					Date	Name	Customer-No.			
TOLERANCE						Drawn	02.09.2019	Winnie	ASSMANN WSW-No. A-TB-3500-xx-F50		
X.	±0.50					Approved	02.09.2019	Winnie			
X.X	±0.30										
X.XX	±0.20										
DIM	TOL								Drawing-No.	rev00	
X.°	±5°										
		①	Drawn	02.09.2019	Winnie						Replace
Angle	TOL	Id.	Modification	Date	Name						