


Ratings and characteristics of Fuji IGBT (MOS FET) Module

6MBI75J-060 (TENTATIVE)

1. Outline Drawing

Unit : mm

= Isolation Voltage : AC 2500 V 1 minute



This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.


g) Revised page 2-4 and added page 4-11. Dec. 17 '72. A. Yamaguchi
b) Revised page 7. Jan. 21 '73. A. Yamaguchi
c) Revised page 8. Jan. 21 '73. A. Yamaguchi
d) Revised page 3, 4, 7, 10. Apr. 6 '73. A. Yamaguchi

	DATE	NAME	APPROVED
DRAWN	Aug. -31-73	H. Arikawa	
CHECKED	Aug. 31-73	T. Hiyasaka	


Fuji Electric Co., Ltd.	
DWG. NO.	<b>MT5F4705</b>
	1/1

MA4LE

2. Equivalent Circuit of Module



3. Equivalent Circuit



4. Absolute Maximum Ratings (Tj=25 °C)

Items	Symbols	Ratings	Units	
Collector-emitter voltage	$V_{CES}$	500	V	
Gate-emitter voltage	$V_{GES}$	$\pm 20$	V	
Collector current	Continuous	$I_c$	7.5	A
	1 ms	$I_c$ pulse	15.0	
		$-I_c$	7.5	
	1 ms	$-I_c$ pulse	15.0	
Max. power dissipation	PC	2.45	W	
Operating temperature	$T_j$	+150	°C	
Storage temperature	$T_{stg}$	-40 ~ +125	°C	
Isolation voltage	$V_{is}$	AC 2500 (1 min)	V	
Screw Torque	Mounting * 1	3.5	N · m	
	Terminals * 2	1.7		

Note : \*1 Recommendable Value : 2.5 ~ 3.5 N · m (M5)  
 Note : \*2 Recommendable Value : 1.3 ~ 1.7 N · m (M4)

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever, for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

REVISIONS			
-----------	--	--	--

DATE	NAME	APPROVED	Fuji Electric Co., Ltd.					
DRAWN	-		DWG. NO.	NT5F4705				
CHECKED	-				2/11	<table border="1"> <tr><td>a</td></tr> <tr><td>b</td></tr> <tr><td>c</td></tr> <tr><td>d</td></tr> </table>	a	b
a								
b								
c								
d								

MA4LE

5. Static electrical characteristics ( at  $T_j=25^\circ\text{C}$  unless otherwise specified )

Items	Symbols	Characteristics			Conditions	Units
		min.	typ.	max.		
Zero gate voltage collector current	$I_{CES}$			1.0	$T_j = 25^\circ\text{C}$ $V_{GE} = 0\text{V}$	mA
					$T_j = 125^\circ\text{C}$ $V_{CR} = 600\text{V}$	mA
Gate-emitter leakage current	$I_{GBS}$			15	$V_{CR} = 0\text{V}$ $V_{GR} = \pm 20\text{V}$	$\mu\text{A}$
Gate-emitter threshold voltage	$V_{GE(th)}$	3.5	5.0	6.5	$V_{CR} = 20\text{V}$ $I_C = 75\text{mA}$	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		1.7	2.5	$V_{CK} = 15\text{V}$ $I_C = 75\text{A}$	V

6. Dynamic ratings ( at  $T_j=25^\circ\text{C}$  unless otherwise specified )

Items	Symbols	Characteristics			Conditions	Units
		min.	typ.	max.		
Input capacitance	$C_{ies}$		4800		$V_{GE} = 0\text{V}$	pF
Output capacitance	$C_{oes}$				$V_{CE} = 10\text{V}$	
Reverse transfer capacitance	$C_{res}$				$f = 1\text{MHz}$	
Turn-on time	$t_{on}$		0.6	1.2	$V_{CC} = 300\text{V}$ $I_C = 75\text{A}$ $V_{GR} = \pm 15\text{V}$ $R_C = 33\Omega$	$\mu\text{s}$
	$t_r$		0.2	0.6		
Turn-off time	$t_{off}$		0.8	1.5		
	$t_f$		0.15	0.35		

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

REVISIONS			
-----------	--	--	--

	DATE	NAME	APPROVED	Fuji Electric Co., Ltd.					
DRAWN	- -			DWG. NO.	3/11				
CHECKED	- -								
				<b>MT5F4705</b>	<table border="1"> <tr><td>21</td></tr> <tr><td>0</td></tr> <tr><td>2</td></tr> <tr><td>0</td></tr> </table>	21	0	2	0
21									
0									
2									
0									

MA4LE

7. Characteristics of reverse diode ( at  $T_j=25^\circ\text{C}$  unless otherwise specified )

Items	Symbols	Characteristics			Conditions	Units
		min.	typ.	max.		
Diode forward on-voltage	$V_F$		2.3	3.0	$I_F = 75\text{A}$ $V_{GE} = 0\text{V}$	V
Reverse recovery time	$t_{rr}$			300	$I_F = 75\text{A}$ $di/dt = 225\text{A}/\mu\text{s}$	ns

8. Thermal resistance characteristics

Items	Symbols	Characteristics			Conditions	Units
		min.	typ.	max.		
Thermal resistance	$R_{th(j-c)}$			0.51	IGBT	$^\circ\text{C}/\text{W}$
	$R_{th(j-c)}$			1.06	Diode	
	* $R_{th(c-f)}$		0.05		the base to cooling fin	

\* This is the value which is defined mounting on the additional cooling fin with thermal compound.

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

REVISIONS		DATE	NAME	APPROVED	Fuji Electric Co., Ltd.	DWG. NO.	<b>MT5F 4705</b>	4/11	A
	DRAWN	- -							B
	CHECKED	- -							C

MA4LE