

规格 Specifications

额定负荷 Ratings	5A 125VAC 3A 250VAC
接触阻抗 Contact Resistance	100 mΩ Max.
绝缘阻抗 Insulation Resistance	DC500 V 60 ± 5 Sec. 100 MΩ Min.
抗电强度 Dielectric Voltage	AC1000 V(50~60HZ) 60 ± 5 Sec.
操作力 Operating Force	35±15 gf
回复力 Releasing Force	5 gf Min.
动作位置 Operating Position	9.40±1.0mm
自由位置 Free Position	12.50mm Max.
接触行程 Pre Travel	3.00 mm Max.
过行程 Over Travel	1.0 mm Min.
差程 Movement Differential Travel	1.0 mm Max.
机械寿命 Operating Life Without Load	1,000,000 次cycles
负荷寿命 Operating Life With Load	UL: 6,000 次cycles
	CQC: 50,000 次cycles
	VDE: 50,000 次cycles

注: P处代表生产日期: YY代表年份=04, 05, 06, ..., M代表季度=1, 2, 3, ...,





示意图 CHEMATIC



安装孔 PIERCING PLAN

序号 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS
11	杠杆 Lever	SUS	1	
10	NO 端子 NO Terminal	Cu/Ep.Ag	1	
9	NC 端子 NC Terminal	Cu/Ep.Ag	1	
8	端子触点 Terminal contact	AgNi10	2	
7	动片触点 Contact	AgNi10	1	
6	动片 Moving Plate	Cu/Ep.Ag	1	
5	弹簧 Spring	SUS	1	
4	COM 端子 Com Terminal	Cu/Ep.Ag	1	
3	按钮 Knob	PBT	1	
2	胶壳 Housing	PBT	1	
1	胶盖 Cover	PBT	1	

标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM2416			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE		ITEM NO	
UNDER 1	± 0.10	MICRO SWITCHES		MS-105A01-01 (B)	
1 - 10	± 0.30	DRAWN	Fang y	VERSION	01
OVER 10	± 0.50	REVIEWED	Zhang n m	SCALE	
		APPROVED	Gao hong	PROJECTION	UNIT mm

COMAX INDUSTRIAL CO., LTD .