


Screw Clamp 35 mm DIN-Rail Terminals
Neutral

WNT 2.5

WNT 4

WNT 6

WNT 10



Dimensions

Width/Length/Height mm (in.)	With TS 35 x 7.5	5 / 60 / 47 (.197"/2.36"/1.85")	6 / 60 / 47 (.24"/2.36"/1.85")	8 / 60 / 47 (.31"/2.36"/1.85")	10 / 60 / 47 (.39"/2.36"/1.85")
	With TS 32	-	-	-	-

Insulation stripping length	mm (in.)	10 (.39")	10 (.39")	12 (.47")	12 (.47")
-----------------------------	----------	-----------	-----------	-----------	-----------

Technical data

Rated voltage/current/wire size	UL	600V / 25A / #22...12 AWG	600V / 35 A / #22...10 AWG	600V / 45A / #20... 8 AWG	600V / 60A / #16... 8 AWG
	CSA	600V / 20A / #26...12 AWG	600V / 35 A / #26...10 AWG	600V / 45A / #20... 8 AWG	600V / 65A / #16... 6 AWG
	VDE	400VAC / 24A / 2.5mm ²	400VAC / 32A / 4mm ²	400VAC / 41A / 6mm ²	400VAC / 57A / 10mm ²

Torque	Nm (lb. in.)	0.8 (7.1)	1.0 (9.0)	1.6 (14.2)	2.3 (20.4)
Clamping screw	M	2.5	3	3.5	4

Ordering data

For 10x3 busbars	Version	Blue Wemid	101068	Blue Wemid	101078	Blue Wemid	101088	Blue Wemid	101098
	For 6x6 busbars	Blue Wemid	101158	Blue Wemid	101178	Blue Wemid	101198	Blue Wemid	101218

End plate

	WAP (thickness 1.5 mm)		Type	Cat. No.	Type	Cat. No.	Type	Cat. No.	Type	Cat. No.
	Blue Wemid	WAP 2.5...10	105008	WAP 2.5...10	105008	WAP 2.5...10	105008	WAP 2.5...10	105008	

Support bracket

	WHP for 10x3 SSch	Blue Wemid	WHP 2.5...10	105028	WHP 2.5...10	105028	WHP 2.5...10	105028	WHP 2.5...10	105028
	WHP for 6x6 SSch	Blue Wemid	WHP 2.5...10	105048	WHP 2.5...10	105048	WHP 2.5...10	105048	WHP 2.5...10	105048
	Thickness 1.5 mm									

Busbar

	10 x 3	SSch 10x3 Cu	34890	SSch 10x3 Cu	34890	SSch 10x3 Cu	34890	SSch 10x3 Cu	34890
		SSch 10x3 Brass	25980	SSch 10x3 Brass	25980	SSch 10x3 Brass	25980	SSch 10x3 Brass	25980
	6 x 6	SSch 6x6 Cu	57130	SSch 6x6 Cu	57130	SSch 6x6 Cu	57130	SSch 6x6 Cu	57130
		SSch 6x6 Brass	57120	SSch 6x6 Brass	57120	SSch 6x6 Brass	57120	SSch 6x6 Brass	57120

Clamping yoke

	For 10 x 3 SSch	ZB 4 K [*]	47538	ZB 4 K [*]	47538	ZB 4 K [*]	47538	ZB 4 K [*]	47538
		ZBE 6 K ^{**}	52598	ZBE 6 K ^{**}	52598	ZBE 6 K ^{**}	52598	ZBE 6 K ^{**}	52598
		ZB 16 K [†]	50288	ZB 16 K [†]	50288	ZB 16 K [†]	50288	ZB 16 K [†]	50288
		ZB 35 K ^{††}	50268	ZB 35 K ^{††}	50268	ZB 35 K ^{††}	50268	ZB 35 K ^{††}	50268
Supply via clamping yoke, for example	For 6 x 6 SSch	ZB 4/6 K [‡]	56548	ZB 4/6 K [‡]	56548	ZB 4/6 K [‡]	56548	ZB 4/6 K [‡]	56548
		ZB 16/6 K ^{‡‡}	56968	ZB 16/6 K ^{‡‡}	56968	ZB 16/6 K ^{‡‡}	56968	ZB 16/6 K ^{‡‡}	56968

Test plug

	For #18 AWG wire	PS 2.3	18040	PS 2.3	18040	PS 2.3	18040	PS 2.3	18040
	For #12 AWG wire								

Marking tags

Note: Part numbers are shown for a single card of pre-printed tags numbered 1-50. For additional information, see section 5.	Consecutive horizontal	Print	FW 5	473460001	FW 6	468660001	FW 8	1653340001	FW 8	1653340001
	Consecutive vertical		FS 5	473560001	FS 6	468760001	FS 8	1653350001	FS 8	1653350001

See Section 5 for mounting rails, end brackets, additional marking material and accessories

^{*}(0.5...4) mm² ^{**}(1.5...10) mm² [†](2.5...16) mm² ^{††}(16...35) mm² [‡](0.5...4) mm² ^{‡‡}(2.5...16) mm²

