


## Locking Fork Terminals



Stock thickness same as ring terminal of same size.

### Vinyl Insulated Locking Fork—Expanded Insulation Support

| Cat. No.   | Bulk Cat. No. | Pkg. Qty. | Wire Range | Max. Ins. | Wt./lbs. Bolt Hole | Per 1000 | Dimensions |     |     |     |
|------------|---------------|-----------|------------|-----------|--------------------|----------|------------|-----|-----|-----|
|            |               |           |            |           |                    |          | A          | B   | C   | M   |
| 18RA-6FLX  | —             | 100       | 22-16      | .170      | #6                 | 5        | .97        | .25 | .25 | .81 |
| 18RA-8FLX  | —             | 100       | 22-16      | .170      | #8                 | 5        | .97        | .29 | .25 | .81 |
| 18RA-10FLX | RA2257-170    | 100/1M    | 22-16      | .170      | #10                | 5        | .97        | .29 | .25 | .81 |
| 14RB-6FLX  | RB2207-200    | 100/1M    | 18-14      | .200      | #6                 | 6        | .97        | .31 | .27 | .81 |
| —          | RB2217-200    | 1000      | 18-14      | .200      | #6                 | 6        | .97        | .29 | .27 | .81 |
| 14RB-8FLX  | RB2237-200    | 100/1M    | 18-14      | .200      | #8                 | 6        | .97        | .31 | .27 | .81 |
| 14RB-10FLX | RB2257-200    | 100/1M    | 18-14      | .200      | #10                | 6        | .97        | .31 | .27 | .81 |
| 10RC-6FLX  | RC2207-250    | 50/500    | 12-10      | .250      | #6                 | 8        | 1.07       | .31 | .27 | .91 |
| 10RC-8FLX  | —             | 50        | 12-10      | .250      | #8                 | 8        | 1.10       | .37 | .27 | .91 |
| 10RC-10FLX | RC2227-250    | 50/500    | 12-10      | .250      | #10                | 8        | 1.10       | .37 | .27 | .91 |
| 10RC-14FLX | —             | 50        | 12-10      | .250      | ¼"                 | 8        | 1.22       | .50 | .32 | .96 |


U.L. Listed E-9809

Installing tools: ERG-2001, ERG-2003, WT145C, WT2000, WT112M, WT1455

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (12050 tool and application dies). See page C61.

Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

### Heat Shrinkable Locking Fork Terminals—Expanded Insulation Support



| Cat. No.    | Pkg. Qty. | Wire Range | Max. Ins. | Bolt Hole | Wt./lbs Per 1000 | Dimensions |     |
|-------------|-----------|------------|-----------|-----------|------------------|------------|-----|
|             |           |            |           |           |                  | A          | B   |
| RAS18-6FLX  | 100       | 22-18      | .170      | #6        | 5                | 1.350      | .25 |
| RAS18-8FLX  | 100       | 22-18      | .170      | #8        | 5                | 1.350      | .29 |
| RAS18-10FLX | 100       | 22-18      | .170      | #10       | 5                | 1.350      | .29 |
| RBS14-6FLX  | 100       | 16-14      | .200      | #6        | 6                | 1.350      | .25 |
| RBS14-8FLX  | 100       | 16-14      | .200      | #8        | 6                | 1.350      | .29 |
| RBS14-10FLX | 100       | 16-14      | .200      | #10       | 6                | 1.350      | .29 |
| RCS10-6FLX  | 50        | 12-10      | .250      | #6        | 8                | 1.350      | .31 |
| RCS10-8FLX  | 50        | 12-10      | .250      | #8        | 8                | 1.350      | .37 |
| RCS10-10FLX | 50        | 12-10      | .250      | #10       | 8                | 1.350      | .37 |
| RCS10-14FLX | 50        | 12-10      | .250      | ¼"        | 8                | 1.350      | .49 |

U.L. Listed E-9809

Installing tool: WT1255

Heat Shrinkable terminals not available on Mylar Tape.

For Mil Specs listing, please refer to page C73.