



RS1032-1

- Designed for 674.0 MHz CATV Converter LOs
- Nominal Insertion Phase Shift of 0° at Resonance
- Quartz Stability
- Rugged, Hermetic, Low-Profile TO39 Case

674.03 MHz SAW Resonator

The RS1032-1 is a two-port surface-acoustic-wave (SAW) resonator in a low-profile TO39 case. It provides reliable, fundamental-mode, quartz frequency stabilization of fixed-frequency oscillators operating at or near 674 MHz. Typical applications include the second LO in CATV set-top converters with channel 3 output.



TO39-3 Case

Absolute Maximum Ratings

Rating	Value	Units
CW RF Power Dissipation (See: Typical Test Circuit.)	+5	dBm
DC Voltage between Any Two Pins (Observe ESD Precautions.)	±30	VDC
Case Temperature ¹	-40 to +85	°C

Electrical Characteristics

Characteristic	Sym	Notes	Minimum	Typical	Maximum	Units
Center Frequency (+25°C) Absolute Frequency Tolerance from 674.030 MHz	f_c	2, 3, 4, 5	673.930		674.130	MHz
	Δf_c				±100	kHz
Insertion Loss	IL	2, 5, 6		8.3	12.5	dB
Quality Factor	Unloaded Q	5, 6, 7		9,500		
	50 Ω Loaded Q			5,900		
Temperature Stability	Turnover Temperature	6, 7, 8	55	70	85	°C
	Turnover Frequency			$f_c + 50$		kHz
	Frequency Temperature Coefficient		FTC		0.037	
Frequency Aging	Absolute Value during the First Year	f_A	6	≤ 10		ppm/yr
DC Insulation Resistance between Any Two Pins		5	1.0			MΩ
RF Equivalent RLC Model	Motional Resistance	5, 7, 9		160	322	Ω
	Motional Inductance			360.609		μH
	Motional Capacitance			0.154613		fF
	Shunt Static Capacitance		C_O	5, 6, 9	1.3	1.6

Lid Symbolization (in Addition to Lot and/or Date Codes)

RFM 1032-1



CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.

NOTES:

1. Frequency aging is the change in f_c with time and is specified at +65°C or less. Aging may exceed the specification for prolonged temperatures above +65°C. Typically, aging is greatest the first year after manufacture, decreasing in subsequent years.
2. The frequency f_c is the frequency of minimum IL with the resonator in the specified test fixture in a 50 Ω test system with VSWR ≤ 1.2:1. Typically, $f_{OSCILLATOR}$ or $f_{TRANSMITTER}$ is less than the resonator f_c .
3. One or more of the following United States patents apply: 4,454,488; 4,616,197.
4. Typically, equipment utilizing this device requires emissions testing and government approval, which is the responsibility of the equipment manufacturer.
5. Unless noted otherwise, case temperature $T_C = +25^\circ\text{C} \pm 2^\circ\text{C}$.
6. The design, manufacturing process, and specifications of this device are subject to change without notice.
7. Derived mathematically from one or more of the following directly measured parameters: f_c , IL, 3 dB bandwidth, f_c versus T_C , and C_O .
8. Turnover temperature, T_O , is the temperature of maximum (or turnover) frequency, f_O . The nominal frequency at any case temperature, T_C , may be calculated from: $f = f_O [1 - FTC (T_O - T_C)^2]$. Typically, *oscillator* T_O is 20° less than the specified *resonator* T_O .
9. This equivalent RLC model approximates resonator performance near the resonant frequency and is provided for reference only. The capacitance C_O is the measured static (nonmotional) capacitance between either pin 1 and ground or pin 2 and ground. The measurement includes case parasitic capacitance.

RFM[®]
