










G	RoHS compliant Unit:mm	Scale	Free					Date	Name	Description: Wire-to-board con. Terminal Female		G		
		TOLERANCE					Drawn	29.10.2021	Daniel					
		X.	±0.35				Approved	09.05.2022	Daniel	ASSMANN WSW-No. A-WBT-O001EG-01CR01				
		X.X	±0.25											
H		X.XX	±0.20	②	Update housing shape	09.05.2022	Daniel				Drawing-No. ASS 9062 CO		rev02	H
		X.XXX	±0.15	①	Update terminal dimension	03.03.2022	Daniel							
		DIM	TOL	③	Drawn	29.10.2021	Daniel				Customer-No.		SHEET 2 / 6	
		Angle	TOL	Id.	Modification	Date	Name							

	1	2	3	4	5	6	7	
A	  Notes: Insulator Material: Nylon66+15%GF, UL94V-0, Black Contact Material: Brass, Tin plated Voltage Rating: 250V AC,DC; Current Rating: 5A AC,DC; Withstanding Voltage: 1500V AC/minute; Insulation Resistance: 1000MΩ Min; Contact Resistance: 20mΩ Max; Operation Temperature: -25°C to +85°C; Packing: PE bag.							A
B								B
C								C
D								D
E								E
F								F
G	  Notes: Insulator Material: Nylon66+15%GF, UL94V-0, Black Contact Material: Brass, Tin plated Voltage Rating: 250V AC,DC; Current Rating: 5A AC,DC; Withstanding Voltage: 1500V AC/minute; Insulation Resistance: 1000MΩ Min; Contact Resistance: 20mΩ Max; Operation Temperature: -25°C to +85°C; Packing: PE bag.							G
H								H
	1	2	3	4	5	6	7	SV5024



Notes:

Insulator Material: Nylon66+15%GF, UL94V-0, Black

Contact Material: Brass, Tin plated

Voltage Rating: 250V AC,DC;

Current Rating: 5A AC,DC;




Withstanding Voltage: 1500V AC/minute;

Insulation Resistance: 1000MΩ Min;


Contact Resistance: 20mΩ Max;

Operation Temperature: -25°C to +85°C;

Packing: PE bag.



No. of Contact	DIM A	DIM B
2	NA	6.65
4	3.00	9.65
6	6.00	12.65
8	9.00	15.65
10	12.00	18.65
12	15.00	21.65
14	18.00	24.65
16	21.00	27.65
18	24.00	30.65
20	27.00	33.65
22	30.00	36.65
24	33.00	39.65



CIRCUIT SIZE LAYOUT

RoHS compliant

Unit:mm

Scale	Free					Date	Name	Description: Wire-to-board con. Male Pitch 3.0mm / Angled
TOLERANCE						Drawn	29.10.2021	Daniel
X.	±0.35					Approved	09.05.2022	Daniel
X.X	±0.25							
X.XX	±0.20	②	Update housing shape	09.05.2022	Daniel			
X.XXX	±0.15	①	Update terminal dimension	03.03.2022	Daniel			
DIM	TOL	⑩	Drawn	29.10.2021	Daniel			
Angle	TOL	Id.	Modification	Date	Name			



ASSMANN WSW-No.
A-WBP-O001DA-xxTB01

Drawing-No.
ASS 9062 CO
rev02

Customer-No.
SHEET
3 / 6

