

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 13_SK-50-0-52/199_N



Description

Straight panel receptacle plug, flange mount

Interface standards
MIL-STD-348A/323



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 40 GHz

Mechanical Data

Weight 0.0038 kg

Environmental Data

Operating Temperature -55 °C to 125 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PPO_PPE
Coupling nut	Stainless Steel

Surface Plating

Gold Plating (Nickel underplated)

Related Documents

Outline drawing	DOU-00010496
Catalogue drawing	DCA-00010498
Assembly instruction	DOC-0000187662
Mounting hole	DOU-00010261

Ordering Information

Single package 13_SK-50-0-52/199_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions