



Note:

1.Material:

- 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: Copper alloy,t=0.60mm
- 1.3 Shell: Spcc,t=0.40mm

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min.
- 2.5 Total mating force: 3.0 Kgf Max.
- 2.6 Total unmating force: 0.5 Kgf Min.
- 2.7 Temperature range: -55°C~85°C

ORDER INFORMATION

MDS -PL -XX
 1 2 3

- 1.MINI DIN:SOLDER TYPE
- 2.PLUG
- 3.POSITION:3,4,5,6,7,8

NO.OF CONTACT	3	4	5	6	7	8
PART NO.	MDM-PL-03	MDM-PL-04	MDM-PL-05	MDM-PL-06	MDM-PL-07	MDM-PL-08
POSTTION						



PART NO. MDM-PL-xx

DWG NO. MDM-PL-xx

FILE NO.

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ±0.30
 .XX ±0.20
 .XXX ±0.10
 AWG

DESCRIP TION: MINI DIN MOLDER TYPE(M)長銅管

AREA	REVISIONS	HK	DATE
------	-----------	----	------

煜倫有限公司