



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to

DIN 72594-1
ISO 20860-1



Documents

Assembly instruction

MA_59V042

Material and plating

Connector parts

- Center contact
- Center contact 2
- Outer contact
- Body
- Dielectric
- Chrimp ferrule
- Cover

Material

- Spring bronze
- Brass
- Spring bronze
- Brass
- PBT
- Copper
- Alpaca

Plating

- Gold, min. 0.8 µm, over chemical nickel
- Gold, min. 0.15 µm, over chemical nickel
- Nickel, 2.5-5 µm
- Nickel, 2.5-5 µm

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09.14/6.2

Electrical data

Impedance	50 Ω
Frequency	DC to 6 GHz
Return loss	≥ 26 dB, DC to 1 GHz ≥ 24 dB, DC to 3 GHz ≥ 17 dB, DC to 6 GHz
Insertion loss	≤ 0.1 x √f(GHz) dB @ 1GHz
Insulation resistance	≥ 1x10 ³ MΩ
Center contact resistance	≤ 15 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage	750 V rms
Working voltage	335 V rms
Power current	≤ 1 A DC
RF-leakage	≥ 65 dB up to 1 GHz

- Limitations are possible due to the used cable type -

Mechanical data

Mating cycles	min. 25
Engagement force	≤ 25 N
Disengagement force	≥ 2 N

Environmental data

Temperature range	-40°C to +105°C
Thermal shock	DIN 72594-2 clause 8.2
Temperature and humidity	DIN 72594-2 clause 8.3
Vibration and mechanical shock	DIN 72594-2 clause 8.1
Dry heat	DIN 72594-2 clause 8.4
RoHS	compliant

- Limitations are possible due to the used cable type -

Tooling

Crimping tool	11W150-000
Crimp insert	11W150-504

Suitable cables

Cable type	RTK 031
------------	---------

Packing

Standard	1000 pcs in box, 4000 pcs in returnable container
Weight	2,57 g/pce

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09.14/6.2

Change Historie

Rev.	Date	Change
d00	02.11.15	Drawing: -tolerance added to 11.3 (11.3±0.1) and 3.9 (3.9-0.07) Interface: -ISO 20860-1 added Environmental data: - Environmental data specification changed from " DIN 72594-2 clause 6.x" to "...8.x" - specification changed from "2002/95/EC (RoHS)" to "RoHS"
e00	08.06.16	new picture of the drawing

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
W. Lankes	15.02.07	C. Anfang	08.06.16	e00	16-0902	T. Koschel	08.06.16
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel. : +49 8684 18-0 Email : info@rosenberger.de		Page 3 / 3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Rosenberger:](#)

[59K28H-1M4A4](#)