



MATERIAL:

- SHELL : DIE CAST ALUMINUM ALLOY PER SAE AMS-QQ-A-591
- INSERT RETAINING PLATES : DIE CAST ALUMINUM ALLOY PER SAE AMS-QQ-A-591
- INSERTS : THERMOSETTING MOLDED COMPOUND PER ASTM D 5948
- GROMMET AND INTERFACIAL SEAL : FLUOROSILICONE ELASTOMER PER SAE AMS-R-25988
- CONTACT RETENTION CLIPS : BERYLLIUM COPPER PER ASTM B 194
- POLARIZING RETENTION PLATE : DIE CAST ALUMINUM ALLOY PER SAE AMS-QQ-A-591
- POLARIZING KEYS : ZINC ALLOY PER ASTM B 86
- SCREWS AND WASHERS: CORROSION RESISTANT MATERIAL

FINISH:

- SHELL : YELLOW CHROMATE OVER CADMIUM PER SAE AMS-QQ-P-416, TYPE II
- INSERT RETAINING PLATES : BLUE EPOXY PAINT
- POLARIZING RETENTION PLATE : YELLOW CHROMATE OVER CADMIUM PER SAE AMS-QQ-P-416, TYPE II,
BLUE EPOXY PAINTED
- POLARIZING KEYS : YELLOW CHROMATE OVER CADMIUM PER SAE AMS-QQ-P-416, TYPE II
- CONTACT BODY : PLATING .00005 INCH OF GOLD PER SAE AMS-2422 OVER NICKEL PER AMS 2403

CONNECTOR FITTED WITHOUT CONTACT :

- MARKING : CONNECTOR MUST BE MARKED WITH : DSXE2RX26PX26P03** + DATE CODE
- INDIVIDUAL PACKAGING

4112_9311 This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.