



Micro Commercial Components  
 20736 Marilla Street Chatsworth  
 CA 91311  
 Phone: (818) 701-4933  
 Fax: (818) 701-4939

# MMBR901

## Description

- High Current-Gain – Bandwidth Products
- Low Noise Figure @  $f=1.0\text{GHz}$  –  $NF_{(\text{matched})}=1.9\text{dB}$  (Typ)
- High Power Gain –  $G_{pe(\text{matched})}=12.0\text{dB}$  (Typ) @  $f=1.0\text{GHz}$
- Operating & Storage Temperature:  $-55^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$
- Marking Code: 7A

## MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	$V_{CE0}$	15	Vdc
Collector-Base Voltage	$V_{CBO}$	25	Vdc
Emitter-Base Voltage	$V_{EBO}$	2.0	Vdc
Collector Current - Continuous	$I_C$	30	mAdc
Thermal Resistance, Junction to Case	$R_{\theta JC}$	250	$^{\circ}\text{C/W}$
Power Dissipation @ $TC=75^{\circ}\text{C}$ (1) Derate above $75^{\circ}\text{C}$	$P_{D(\text{max})}$	0.300 4.0	Watt mW/ $^{\circ}\text{C}$

## Electrical Characteristics @ $25^{\circ}\text{C}$ Unless Otherwise Noted

Characteristics	Symbol	Min	Max	Unit
-----------------	--------	-----	-----	------

## OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage ( $I_C = 1.0\text{mAdc}$ , $I_E = 0$ )	$V_{(BR)CEO}$	15		Vdc
Collector-Base Breakdown Voltage ( $I_C = 0.1\text{mAdc}$ , $I_E = 0$ )	$V_{(BR)CBO}$	25		Vdc
Emitter-Base Breakdown Voltage ( $I_E = 0.1\text{mAdc}$ , $I_C = 0$ )	$V_{(BR)EBO}$	2.0		Vdc
Collector Cutoff Current ( $V_{CB} = 15\text{Vdc}$ , $I_E = 0$ )	$I_{CBO}$		50	NAdc

## ON CHARACTERISTICS



DC Current Gain ( $I_C = 5.0\text{mAdc}$ , $V_{CE} = 5.0\text{Vdc}$ )	$h_{FE}$	50	200	
--	----------	----	-----	--

## SMALL-SIGNAL CHARACTERISTICS

Output Capacitance ( $V_{CB} = 10\text{Vdc}$ , $I_C = 5.0\text{mAdc}$ , $f = 1.0\text{GHz}$ )	Cobo		1.0	pF
Common-Emitter Amplifier Gain ( $V_{CC} = 6.0\text{Vdc}$ , $I_C = 5.0\text{mAdc}$ , $f = 1.0\text{GHz}$ )	$G_{pe}$		12	dB

**Note:** 1. Case temperature measured on collector lead immediately adjacent to body of package

## NPN Silicon High-Frequency Transistor



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.110	.120	2.80	3.04	
B	.083	.098	2.10	2.64	
C	.047	.055	1.20	1.40	
D	.035	.041	.89	1.03	
E	.070	.081	1.78	2.05	
F	.018	.024	.45	.60	
G	.0005	.0039	.013	.100	
H	.035	.044	.89	1.12	
J	.003	.007	.085	.180	
K	.015	.020	.37	.51	

## Suggested Solder Pad Layout

