



PRODUCT INFORMATION

835nm

1A279
High-Performance LED

Position Sensors

This device features broad spectral width which makes it ideal in certain sensor applications. It operates in a wide temperature range and delivers high power to large-core fiber, making it ideal for WDM-based position sensors in aircraft.



TO-46 Package With Lens

Optical and Electrical Characteristics (25°C Case Temperature)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Fiber-Coupled Power (Fig. 1, 2, & 3) (Table 1)	P_{fiber}	300	400		μW	$I_F=100\text{ mA}$ (Note 1) Fiber: 100/140 μm
Rise and Fall Time (10-90%)	t_r, t_f		20		ns	$I_F=100\text{ mA}$ (no bias) Step Index
Bandwidth (3dB _{e1})	f_c		15		MHz	$I_F=100\text{ mA}$ NA=0.22
Center Wavelength (Fig. 6)	λ_c		835		nm	$I_F=100\text{ mA}$
Spectral Width (FWHM)	$\Delta\lambda$		120		nm	$I_F=100\text{ mA}$
Forward Voltage (Fig. 5)	V_F		2.3		V	$I_F=100\text{ mA}$
Reverse Current	I_R		20		μA	$V_R=1\text{ V}$
Capacitance	C		250		pF	$V_R=0\text{ V}, f=1\text{ MHz}$

Note 1: Measured at the exit of 100 meters of fiber.

Absolute Maximum Ratings

PARAMETER	SYMBOL	LIMIT
Storage Temperature	T_{stg}	-55 to +125°C
Operating Temperature (derating: Fig. 4)	T_{op}	-55 to +125°C
Electrical Power Dissipation (derating: Fig. 4)	P_{tot}	250 mW
Continuous Forward Current ($f \leq 10\text{ kHz}$)	I_F	110 mA
Peak Forward Current (duty cycle $\leq 50\%$, $f \geq 1\text{ MHz}$)	I_{FRM}	180 mA
Reverse Voltage	V_R	1.5 V
Soldering Temperature (2mm from the case for 10 sec)	T_{sld}	260°C

Thermal Characteristics

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
Thermal Resistance - Infinite Heat Sink	R_{thjc}		100		°C/W
Thermal Resistance - No Heat Sink	R_{thja}		400		°C/W
Temperature Coefficient - Optical Power	dP/dT_j		-0.5		%/°C
Temperature Coefficient - Wavelength	$d\lambda/dT_j$		0.3		nm/°C

12261.11 1994-09-20



Europe: Tel (46) 8 58 02 45 00 Fax (46) 8 58 02 01 10
Tel (44) 1291 436180 Fax (44) 1291 436771

America: Tel 1-800-96MITEL Fax (613) 592-6909
Asia: Tel (65) 293 5312 Fax (65) 293 8527

Typical Fiber-Coupled Power			
Core Diameter/Cladding Diameter Numerical Aperture			
50/125 μm 0.20	62.5/125 μm 0.275	100/140 μm 0.29	200/230 μm 0.37
60 μW	150 μW	400 μW	800 μW

Table 1

