


SRMB2.5/2

- 4 Connections
- Direct mounting





PTR

Phoenix Mecano Brand

Technical Data

Wire sizes		Insulating Material	
Solid min	0.2 mm ²	Material	PA 6.6
Solid max	4.0 mm ²	Flammability Class	UL 94 V-2
Stranded (flexible) min	0.2mm ²	Temperatures	
Stranded (flexible) max	4.0 mm ²	Working Temperature	-40 - 105 °C
Stranded with Ferrule min	0.2 mm ²	Dimensions	
Stranded with Ferrule max	2.5 mm ²	Stripped Length	7.0 mm
Clamping Range min	0.2mm ²	Width	5.0 mm
Clamping Range max	4.0 mm ²	Height	23.0 mm
		Length	24.5 mm
		Length Hole Direct Mounting	17.4 mm

Colours

	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015

Connection Diagram



Order Data

Article Designation	Article Number	PU
SRMB2.5/2-BEIGE	41321.2	50
SRMB2.5/2-BLUE	41321.5	50

Accessoires

Article Designation	Article Number	PU
External Cross-Connector insulated AQI2/5/11	492032.0	50
External Cross-Connector insulated AQI3/5/11	492033.0	50
External Cross-Connector insulated AQI4/5/11	492044.0	10
External Cross-Connector insulated AQI10/5/11	492045.0	10
Quick Labelling PSB5/50	494600.7	500

Ratings

Ratings	UR		IEC
	Rated Voltage	300 V	300 V
Rated Current	20 A	20 A	24 A
Rated Wire Size	AWG 22-12	AWG 22-12	2.5 mm ²
Rated Impulse Voltage			6 V
Pollution Degree			3