



RECOMMENDED MOUNTING HOLE
(建議架設孔)

5	NUT	NOTE 1	NOTE 2	1
4	WASHER	NOTE 5	NOTE 2	1
3	CONTACT PIN	NOTE 1	NOTE 3	1
2	INSULATOR	NOTE 4	WHITE	1
1	BODY	NOTE 1	NOTE 2	1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
- BRASS PER QQ-B-626
 - GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
 - GOLD PL 30 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
 - TEFLON MIL-P-19468
 - BRASS PER QQ-B-613

MAX. PANEL THICKNESS=2.4mm
(最大板厚)

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 .XX ±0.25 ANG. ±5°				
PART No. SMB-JSR		MEI						
DRAWING No. SMB-JSR		CHECKED BY BECKY						
SCALE NONE		DRAWING BY TCF						
SCALE	NONE	REV.	A0	UNIT mm	⊕	△ A0 NEW RELEASE		
						NO. REV.	REVISIONS	CHK DATE