



**SIDE ENTRY  
PCB SOCKET**

No. Of Positions	Dimensions			
	A	B	C	D
4	13.72 .540	11.26 .443	7.62 .300	3.81 .150
6	15.75 .620	13.21 .520	10.16 .400	6.35 .250
8	17.78 .700	15.24 .600	11.43 .450	8.89 .350

**Technical Data**

**Housing :** Standard Material : Glass Filled NYLON 66 UL94V-0  
 Standard Colour : Black  
 Optional Colour : Medium Gray

- Gold Plating :**
1. 0.38 $\mu$  m/15 $\mu$  inch minimum
  2. 0.76 $\mu$  m/30 $\mu$  inch minimum
  3. 1.27 $\mu$  m/50 $\mu$  inch minimum
  4. 0.15 $\mu$  m/6  $\mu$  inch minimum
  5. Palladium Plating

**Contact :** 0.35mm (0.014") Thickness Phosphor Bronze Selective  
 Gold Plating Over Nickel

**Ordering Data**

Part Number	No. Of Positions	No. Of Contacts	Gold Plating	Part Number	No. Of Positions	No. Of Contacts	Gold Plating
9634-01	4	4	1	9636-13	6	4	3
9634-02	4	4	2	9636-14	6	4	4
9634-03	4	4	3	9636-15	6	4	5
9634-04	4	4	4	9636-21	6	2	1
9634-05	4	4	5	9636-22	6	2	2
9636-01	6	6	1	9636-23	6	2	3
9636-02	6	6	2	9636-24	6	2	4
9636-03	6	6	3	9638-01	8	8	1
9636-04	6	6	4	9638-02	8	8	2
9636-05	6	6	5	9638-03	8	8	3
9636-11	6	4	1	9638-04	8	8	4
9636-12	6	4	2	9638-05	8	8	5