







.250 Quick-Connect Series
In-Line Type

— Cross Bridge Design —
 To Accept .250 x .032 Male Tab

STYLE AND DIMENSIONS	WIRE RANGE	INSULATION RANGE	ØL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	22-18	.060-.115	✓ ✓	5000	$\frac{7}{32} \pm \frac{1}{32}$.016	Pre Tinned Brass Brass	3000H 119A-6 3000H 119AB-6
	22-18	None	✓ ✓	5000	$\frac{7}{32} \pm \frac{1}{32}$.016	Pre Tinned Brass Brass	3000H 119A-6-2 3000H 119AB-6-2
	22-18	.060-.115	✓ ✓	5000	$\frac{7}{32} \pm \frac{1}{32}$.016	Silver Plated Brass	3000H 129AC-6
	22-18	None	✓ ✓	5000	$\frac{7}{32} \pm \frac{1}{32}$.016	Silver Plated Brass	3000H 129AC-6-2
	22-16	.075-.125	✓ ✓	5000	$\frac{7}{32} \pm \frac{1}{32}$.016	Pre Tinned Brass Brass	3000H 119A-4 3000H 119AB-4
	22-16	None	✓ ✓	5000	$\frac{7}{32} \pm \frac{1}{32}$.016	Pre Tinned Brass Brass	3000H 119A-4-2 3000H 119AB-4-2

Note: -6 Series will Accept #24-#18 AWG.