



## PICABOND® Connector, 1000 strip, purple/amber

- Lightweight, compact, and economical means of splicing multiconductor telephone cable
- No prestripping or cutting required, can tap without service interruptions, eliminates “turndowns”
- Color-coded to indicate size and type of wire; used for standard load coil, breakaway load coil and breakaway (add slack) splicing applications

## Product Classification

<b>Regional Availability</b>	Australia/New Zealand   EMEA   Latin America   North America
<b>Product Type</b>	Splice
<b>Product Brand</b>	PICABOND®
<b>Product Series</b>	PICABOND

## General Specifications

<b>Connector Color Code</b>	Purple/Amber
<b>Connector Sealant</b>	Gel filled
<b>Connector Splicing Type</b>	Breakaway (add slack)   Breakaway Load Coil   Standard Load Coil

## Dimensions

<b>Compatible Conductor Gauge, solid</b>	26–22 AWG
--	-----------

## Electrical Specifications

<b>Safety Voltage Rating</b>	400 Vdc
------------------------------	---------

## Material Specifications

<b>Contact Base Material</b>	Phosphor bronze
<b>Contact Plating Material</b>	Tin
<b>Insulation Material</b>	Air Core PIC   Foam Filled PIC

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +60 °C (-40 °F to +140 °F)
<b>Environmental Space</b>	Outdoor

# 552639-1

---

## Packaging and Weights

<b>Packaging quantity</b>	1000
<b>Packaging Type</b>	Strip