

75AU

UHF Female with gas barrier for 7/8 in HJ5-50 air dielectric cable

OBSOLETE

This product was discontinued on: April 1, 2014

Product Classification

Product Type	Air coaxial connector
Product Brand	HELIAX®

General Specifications

Body Style	Straight
Cable Family	HJ5-50
Gas Barrier	Yes
Inner Contact Attachment Method	Self-tapping
Inner Contact Plating	Unplated
Interface	UHF Female
Mounting Angle	Straight
Outer Contact Attachment Method	Tab-flare
Outer Contact Plating	Unplated

Dimensions

Length	78.994 mm 3.11 in
Diameter	35.814 mm 1.41 in
Nominal Size	7/8 in

Electrical Specifications

Insertion Loss, typical	0.05 dB
Average Power at Frequency	0.3 kW @ 900 MHz
Cable Impedance	50 ohm
Connector Impedance	50 ohm
dc Test Voltage	2 kV
Insulation Resistance, minimum	5000 MOhm

75AU

Operating Frequency Band	0 – 5200 MHz
Peak Power, maximum	10 kW
RF Operating Voltage, maximum (vrms)	707 V

Environmental Specifications

Operating Temperature	-40 °C to +150 °C (-40 °F to +302 °F)
Storage Temperature	-70 °C to +100 °C (-94 °F to +212 °F)

Packaging and Weights

Weight, net	0.3 kg 0.661 lb
--------------------	-------------------

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



* Footnotes

Insertion Loss, typical	0.05v̄freq (GHz) (not applicable for elliptical waveguide)
--------------------------------	--